

BIOS Release Notes

TITLE

SUBJECT: MZB3-G43 BIOS Release Notes version F14
System: G593-ZD2-AAX1-000,G593-ZD2-LAX1-000,G593-ZD2-AAX2-000,
G593-ZD2-AAX3-000

About This Release

Build Date: 2025/01/15
BIOS Checksum: 0xBF388D66 (32M)
Release Owner: Neil.Lu

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZB3-G43-000
PCB Version: 1.x,3.x
Microcode updates versions:

| CPUID | Family | Microcode Update ID |
|------------|-------------------------|---------------------|
| Genoa B0 | Family 19h Model 10-1Fh | 0x0A101020 |
| Genoa B1 | Family 19h Model 10-1Fh | 0x0A101148 |
| Genoa B2 | Family 19h Model 10-1Fh | 0x0A101248 |
| Bergamo A0 | Family 19h Model 10-1Fh | 0x0AA00009 |
| Bergamo A1 | Family 19h Model 10-1Fh | 0x0AA00116 |
| Bergamo A2 | Family 19h Model 10-1Fh | 0x0AA00215 |

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT026
AGESA PI version: GenoaPI 1.0.0.D
OPROM version:

| OPROM | Version |
|---------|---------|
| AST2600 | 1.12.00 |

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZB3-G43_F14.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update

BIOS Release Notes

5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\afuwin32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\afuwin64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F14

1. [Feature] Enhance device compatibility.

F13

1. [Fix] Fixed MZB3-G43 G593-ZD2 With GC-MSG4 x12 can't boot os issue.

F12

1. [Bug] Optimize Webui device information such as BCM57416 and ConnectX-5.
2. [Feature] Optimize system.

F11

1. Update AGESA 1.0.0.C.
2. [Bug] Optimize PCIe link speed.
3. [Security Update] PKfail issue.
4. [Feature] Optimize WebUI HDD Inventory information.
5. [Feature] Optimize CX7 WubUI Inventory information.
6. [Feature] Fine tune BMC IPv6 and IPv4 Network.
7. Remove item "Boot mode select".
8. Remove not available Redfish items:
Secure Boot (SECB001)
Boot mode select (FBO001)

BIOS Release Notes

ACPI SLIT local inter-CXL distance (Genoa128)

ACPI SLIT remote inter-CXL distance (Genoa129)

IPv6 BMC Lan Option (IPMI601)

IPv6 BMC Lan IP Address Source (IPMI602)

9. Change item "Endless Retry Boot" Redfish AttributeName from "Genoa834" to "GBT0168" .

10. Secure update: CVE-2023-31355, CVE-2024-21978, CVE-2024-21980, CVE-2023-31315

F10

- 1.Optimize NVME device.
- 2.Optimize SMBIOS information.

F09

- 1.Optimize AC Loss feature. (In Redfish function: only support command "PowerRestorePolicy")

F08

1. Support G593-ZD2-AAX3 system SKU.
2. Enhance PCIe compatibility.

F07

1. Update AGESA 1.0.0.B
2. Support G593-ZD2-AAX2 system.
3. Update re-driver for G593-ZD2-AAX2 system.
4. Secure update: CVE-2023-31346, CVE-2023-31347, CVE-2023-39538, CVE-2023-39539, CVE-2023-45229, CVE-2023-45230, CVE-2023-45231, CVE-2023-45232, CVE-2023-45233, CVE-2023-45234, CVE-2023-45235.

F06

1. Set default year from 2023 to 2024.
2. Fixed X710 LAN Mac issue in Legacy mode.

F05

1. Enhance RedFish function.
2. Fixed yellow bang in windows.
3. Fixed Redfish item fail issue.
4. Enhance NVMe hotplug feature.
5. Added Power btn control item.
6. Update Inventory v07 for G593-ZD2-LAX1

BIOS Release Notes

7. Fine tune SATA information.
8. Update AGESA 1.0.0.A
9. Update Ucode.
10. Support CPU Serial Number in SMBIOS type4
11. Support VGA SEL Log

F04

1. Fixed WebUI NIC information.
2. Fixed Intel X550 or X710 ipref drop performance.
3. Fixed install CX7 * 12 system hang up.
4. Some slot support auto bifurcation.
5. Fixed BIOS recovery
6. Update NVME WebUI information.
7. Modify BIOS Item Default.

F03

1. MZB3-G53(G593-ZD2) First release.
 2. Update AGESA 1.0.0.9.
 3. Update Inventory v02.
-