

BIOS Release Notes

TITLE

SUBJECT: MZG3-GU0 BIOS Release Notes version F13
System: MZG3-GU0-000,R163-ZG2-AAJ2-000,R163-ZG6-AAL2-000,
R263-ZG0-AAL2-000,R263-ZG2-AAJ3-000,R263-ZG5-AAL2-000

About This Release

Build Date: 2025/03/10
BIOS Checksum: 0xBDB6149C (32M)
Release Owner: Jason.Wang1

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZG3-GU0-000
PCB Version: 1.x
Microcode updates versions:

CPUID	Family	Microcode Update ID
Genoa B0	Family 19h Model 10-1Fh	0x0A101020
Genoa B1	Family 19h Model 10-1Fh	0x0A101154
Genoa B2	Family 19h Model 10-1Fh	0x0A10124F
Bergamo A0	Family 19h Model 10-1Fh	0x0AA00009
Bergamo A1	Family 19h Model 10-1Fh	0x0AA00116
Bergamo A2	Family 19h Model 10-1Fh	0x0AA00219

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT027
AGESA PI version: GenoaPI 1.0.0.E
OPROM version:

OPROM	Version
AST2600	1.13.01

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZG3-GU0_F13.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update

BIOS Release Notes

5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\afuwin32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\afuwin64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F13

1. [Fix] Fixed the NVMe hotplug config for R163-ZG2-AAJ2 and R263-ZG0-AAL2 system.

F12

1. [Feature] Update AGESA 1.0.0.E.
2. [Security] CVE-2024-56161, CVE-2024-36347, CVE-2024-38796

F11

1. [Fix] Fixed the NVMe hotplug config for R263-ZG5-AAL2 system.

F10

1. [Feature] Support KMIP.
2. [Fix] Fixed the IPv6 gateway configuration issue on the Server Manager setup page.

F09

- 1.[Fix] Update inventory to version:26 to correct CXL table config.

F08

BIOS Release Notes

- 1.[Fix] Update inventory to version:24 for Web BMC device information table.

F07

- 1.[Fix] Fix the network configuration switching issue in the BIOS Server Manager setup.
- 2.[Fix] Fix the issue where having too many installed devices causes the system to hang at the BIOS logo screen.

F06

- 1.Add new SKU support: R163-ZG6-AAL2-000, R263-ZG5-AAL2-000

F05

1. Update Dual Image version Support.

F04

- 1.[VR Update] Update TI VR rom to version B3.

F03

1. [Bug] PCI Inventory information Mantis: 66281
2. [Bug] Fizz HDD Inventory information Mantis: 66280
3. [Bug] Fix NIC Inventory information Mantis: 66283

F02

1. [Security Update] PKfail issue.
2. [Feature] Optimize WebUI HDD Inventory information.
3. [Feature] Optimize CX7 WebUI Inventory information.

F01

1. First release.
-