

BIOS Release Notes

TITLE

SUBJECT: MZ33-AR0 BIOS Release Notes version F33
System: MZ33-AR0-000,S453-Z30-AAV1-000

About This Release

Build Date: 2024/11/27
BIOS Checksum: 0xBF9233BF (32M)
Release Owner: Auto.Build(Hex.Jan)

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZ33-AR0-000
PCB Version: 1.x,3.x
Microcode updates versions:

CPUID	Family	Microcode Update ID
Genoa B0	Family 19h Model 10-1Fh	0x0A101020
Genoa B1	Family 19h Model 10-1Fh	0x0A101148
Genoa B2	Family 19h Model 10-1Fh	0x0A101248
Bergamo A0	Family 19h Model 10-1Fh	0x0AA00009
Bergamo A1	Family 19h Model 10-1Fh	0x0AA00116
Bergamo A2	Family 19h Model 10-1Fh	0x0AA00215

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT026
AGESA PI version: GenoaPI 1.0.0.D
OPROM version:

OPROM	Version
AST2600	1.12.00

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZ33-AR0_F33.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update
5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS Release Notes

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\afuwin32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\afuwin64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F33

- 1.[Feature] Update AGESA 1.0.0.D.
- 2.[Fix] Fix the network configuration switching issue in the BIOS Server Manager setup.
- 3.[Fix] Fix the issue where having too many installed devices causes the system to hang at the BIOS logo screen.

F32

- 1.[Featurer] support AMI BCP PRO tool.

F31

1. [Security Update] PKfail issue.
2. [Feature] Optimize WebUI HDD Inventory information.
3. [Feature] Optimize CX7 WubUI Inventory information.

F30

1. [Feature] Fine tune BMC IPv6 and IPv4 Network.
2. Remove item "Boot mode select".
3. Remove not available Redfish items:
Secure Boot (SECB001)
Boot mode select (FBO001)
ACPI SLIT local inter-CXL distance (Genoa128)
ACPI SLIT remote inter-CXL distance (Genoa129)

BIOS Release Notes

IPv6 BMC Lan Option (IPMI601)

IPv6 BMC Lan IP Address Source (IPMI602)

4. Change item "Endless Retry Boot" Redfish AttributeName from "Genoa834" to "GBT0168" .

5. Update GBT Channel Genoa AGESA 1.0.0.C.

6. Secure update: CVE-2023-31355, CVE-2024-21978, CVE-2024-21980, CVE-2023-31315

F29

1. Optimize GBT Channel Genoa Agesa 1.0.0.C.

F28

1. Update GBT Channel Genoa AGESA 1.0.0.C.

2. Secure update: CVE-2024-21965, CVE-2023-31351, CVE-2023-20582, CVE-2023-31340, CVE-2024-21978, CVE-2024-21980, CVE-2023-31355, CVE-2023-5678, CVE-2023-45236, CVE-2023-45237, CVE-2023-2650, CVE-2023-3817, CVE-2023-31315

F27

1. Update GPU Secure function.

2. Enhance PCIe compatibility.

3. Enhance endless boot feature.

F26

1. Optimize AC Loss feature. (In Redfish function: only support command "PowerRestorePolicy")

F25

1. Enhance PCIe compatibility.

F24

1. Optimize Redfish compatibility.

F23

1. Update GBT Channel Genoa AGESA 1.0.0.B.

2. Support Endless Retry PXE feature.

3. Secure update: CVE-2023-31346, CVE-2023-31347, CVE-2023-39538, CVE-2023-39539, CVE-2023-45229, CVE-2023-45230, CVE-2023-45231, CVE-2023-45232, CVE-2023-45233, CVE-2023-45234, CVE-2023-45235.

BIOS Release Notes

F22

1. Optimize default year 2024.
2. Fixed X710 LAN Mac issue in Legacy mode.
3. Modify MCIO bifurcation .
4. Enhance NVMe Hotplug feature.

F21

1. Add MCIO bifurcation option.

F20

1. Fixed yellow bang in windows.
2. Fixed Redfish item fail issue.
3. Enhance Redfish feature.
4. Enhance NVMe hotplug feature.
5. Added Power btn control item.
6. Optimize SMBIOS compatibility.
7. Update AGESA 1.0.0.A.

F19

1. Enhance Red fish function.

F18

1. Fixed WHLK issue.

F17

1. Optimize SMBIOS compatibility.
2. Optimize PCIe LAN card compatibility.
3. Optimize system inventory compatibility.
5. Update AGESA 1.0.0.9.
6. Fixed system full DIMM reboot issue.
7. Fixed BIOS recovery issue.

F16

1. Remove U2_P0_G2A, U2_P0_G3A & U2_P0_G3B present function.

F15

1. Fixed system reboot when error hold on.
2. Fixed yellow bang in windows.

BIOS Release Notes

F14

1. Adjust U2_P0_G3A and U2_P0_G3B support behavior.

F13

1. Update AGESA 1.0.0.8.
2. Enable MCTP feature.
3. Modify SATA Mode item default from "AHCI AS ID 0X7904" to "ACHI"

F12

1. Adjusted BMC Watch Dog timer.
2. Optimize Chelsio cards compatibility.

F11

1. Support Present function
2. Support MCIO G0.G1.G2 only X4X4X4X4 function/G3 SATA&X4X4X4X4.

F10

1. Update Inventory Mapping system.
2. Fixed COM Port mouse is not working.
3. Added DIMM Manufacturer ID 0x1A08.
4. Fixed NVME LED control failed.
5. Fixed SATA LED Control failed.
6. Adjust the display order of NVME devices list.

F09

1. Support Bergamo CPU.

F08

1. Updated AGESA 1.0.0.5.

F07

1. Fixd PCIE_4 show issue on Web UI.

F06

1. Add S453-Z30-AAV1-000 System.
2. Fixed NVME hot plug function.

BIOS Release Notes

3. Agesa 1.0.0.3.
4. Fixed U2_P0_G0 Gen4 speed issue.

F05

1. pcie slot_6 default auto.

F04

1. PCIE&MCIO default x4x4x4x4.

F03

1. Update AGESA 1.0.0.2.
2. Update Microcode.
3. Support Bergamo CPU.

F02

1. Update AGESA 1.0.0.1

F01

- 1.First Release.
-