

BIOS Release Notes

TITLE

SUBJECT: 7PESH2 BIOS Release Notes version [R15](#)

About This Release

Build Date: [2015/1/14](#)

BIOS Checksum: [0x23871348](#) (4M), [0x4D61D774](#) (8M)

Release Owner: yilun

BIOS Components/Contents

Processor stepping(s) supported: supports Intel® SandyBridge-EP processors

System hardware configurations supported: GA-7PESH2-RH Rev: [0.1/0.2/1.0](#)

Microcode updates versions:

CPUID	Family	Microcode Update ID
206D5	SandyBridge-EP Processor C-0	00000513
206D6	SandyBridge-EP Processor C-1 and M-0	00000619
206D7	SandyBridge-EN -EP Processor C-2 and M-1	00000710
306E2	Ivy Bridge-EP -EX -EN Processor B-1, B-2, L-1, L-2, R-0, and R-1	0000020D
306E3	Ivy Bridge-EP -EX Processor B-3	00000308
306E4	Ivy Bridge -EX -EP -EN Processor C-0, C-1, S-0, S-1, M-0, M-1	00000416
306E6	Ivy Bridge -EX Processor D-0	00000600

IPMI support:

AMI Kernel version: [Gbt_Kernel_F03z7](#)

Intel CSI/MRC Package version: [2.00.03](#)

SPI Descriptor version: [02.01.07.129.2_05](#)

OPROM version :

OPROM	Version
INTEL ASPEED VGA	0.97
INTEL x540	2.1.96
INTEL SAS	3.7

Installation Notes

IMPORTANT NOTES:

1. Please extract the 7PESH2_[R15](#).zip to a bootable diskette that can boot to real DOS
2. Please don't load HIMEM.SYS or any other memory management SW in the diskette

BIOS Release Notes

BIOS UPDATE INSTRUCTIONS FOR DOS:

1. Insert USB flash drive to system for BIOS upgrade
2. Power on system and boot to USB flash
3. Execute FB.BAT for bios update
 - a. Execute "FB.BAT 3" only Flash BIOS Command line
 - b. Execute "FB.BAT 2" need move ME flash jump(AC off) to flash ME firmware
4. After bios flash finish, system will reboot automatically, please do not remove USB flash
5. System will restore DMI data after boot to DOS again, please wait the message below,
"All BIOS flash steps are done! Please AC OFF and AC ON again. Thanks!"
6. Done

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell
3. Execute \Tool\Win32\fb.cmd or \Tool\Win64\fb.cmd for bios update
4. After bios flash finish, Please reboot windows system

BIOS UPDATE INSTRUCTIONS FOR LINUX:

1. Insert bios update USB flash drive.
2. Use Command Shell
3. Execute \Tool\LNx\afulnx32\fb.sh or \Tool\LNx\afulnx64\fb.sh for bios update
4. After bios flash finish, Please reboot windows system

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press F2 during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

R15

1. Fixed issue that system hang on.

R14

1. Modified IO during SMM.

R12

1. Fixed issue that system hang on 0xB0 inserts two CPU.

R11

1. Modified SCU port routing.

R10

1. Fixed issue that Gateway ip can't setting 0.(BMC M/B)
2. Changed Enforce DIMM default to Enforce DIS for some Memmory marge.

BIOS Release Notes

R09

1. Fixed issue that system hang on 0xB1 sometimes.
 2. Changed Enforce DIMM default to Enforce EN for some Memmory marge.
-

R08

1. Fixed issue that insert non-ECC UDIMM can't booting up.
 2. Fixed issue that system hang on 0x2F post code when inserts sandy Bridge CPU.
 3. Fixed issue that BMC IP shows 48.48.48.48 when changed BMC source first time.
 4. Added feature that BMC IP syn on Setup Menu.
-

R07

1. Improve CPU compatible ability.
-

R06

1. Changed oprom shadow policy.
 2. Fixed MRC incorrect.
-

R05

1. System bee sounds when memeory hadn't install.
-

R04

1. Fixed issue that system can't booting when memory error occurs.
-

R03

1. Fixed issue that system hang on when select dymanic pci base
 2. Modified BMC ip setting timing.
 3. Update Microcode
 4. LSI s/w can't update on dos.
 5. Fixed issue system hang on memory initial.
 6. Fan policy item support.
 7. F10 key display.
-

R01

1. uEFI Vga support.
 2. Fan Curver support.
 3. SOL item issue fixed.
 4. VBIOS update to 0.97
-

F22

1. modify fast boot
-

T12

1. Fxied issue that DTM can't pass.
-

T11

BIOS Release Notes

1. BMC Watch Dog support.

T10

1. uEFI onboard VGA support.
2. VBIOS update to 0.97 version.
3. Fixed issue that Lan oprom couldn't be disabled.

T09

1. Ivy Bridge C-1 Step support.

T08

1. Ivy Bridge C-0 CPU support.
2. BMC IP setting policy modified.
3. Fixed issue that Memeoy error occurs didn't display disabled string on setup menu.
4. Info report error default sets enabled.

F20

1. Update SCU oprom to 3.7

F19

1. System Beep when memory uninstall.
2. BMC IP can't setting on Setup Menu.

T07

1. Update MRC to 18
2. Fixed issue that system hang on 0xBF when reboot.
3. AC loss for BMC function support.

T06

1. fixed USB OC issue

T05

1. For Ivy Bridge support.
-