

BIOS Release Notes

TITLE

SUBJECT: MZB3-G43 BIOS Release Notes version F12
System: MZB3-G43-000,G493-ZB0-AAP1-000,G593-ZD1-AAX1-000,
G593-ZD1-AAX2-000,G593-ZD1-AAX3-000,G593-ZD1-LAX1-000,
G593-ZD3-AAX3-000,G593-ZD3-AAX4-000

About This Release

Build Date: 2024/05/17
BIOS Checksum: 0xC11DACC4 (32M)
Release Owner: Neil.Lu

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZB3-G43-000
PCB Version: 1.x
Microcode updates versions:

CPUID	Family	Microcode Update ID
Genoa B0	Family 19h Model 10-1Fh	0x0A101020
Genoa B1	Family 19h Model 10-1Fh	0x0A101144
Genoa B2	Family 19h Model 10-1Fh	0x0A101244
Bergamo A0	Family 19h Model 10-1Fh	0x0AA00009
Bergamo A1	Family 19h Model 10-1Fh	0x0AA00116
Bergamo A2	Family 19h Model 10-1Fh	0x0AA00213

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT024
AGESA PI version: GenoaPI 1.0.0.B
OPROM version:

OPROM	Version
AST2600	1.12.00

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZB3-G43_F12.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number

BIOS Release Notes

4. Execute F.nsh for bios update
5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\Win32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\Win64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F12

1. Optimize WebUI function.

F11

1. Optimize AC Loss feature. (In Redfish function: only support command "PowerRestorePolicy")

F10

1. Support G593-ZD3-AAX3 and G593-ZD3-AAX4 system.
2. Enhance PCIe compatibility.
3. Update Inventory v16.

F09

1. Optimize RedFish compatibility.

F08

1. Update inventory v14.
2. Optimize RedFish feature.
3. Optimize PCIe IRQ.

BIOS Release Notes

4. Fixed POST information incorrect.
5. Modify USB Tree for WHQL.
6. Support G593-ZD1-AAX2 and G593-ZD1-AAX3 system.
7. Update Re-Driver for G593-ZD1-AAX2 and G593-ZD1-AAX3 system.
8. Optimize PCIe topology.

F07

1. Optimize default year 2024.
2. Fixed X710 LAN Mac issue in Legacy mode.

F06

1. Fixed yellow bang in windows.
2. Fixed Redfish item fail issue.
3. Enhance Redfish feature.
4. Enhance NVMe hotplug feature.
5. Added Power btn control item.
6. Optimize SMBIOS compatibility.
7. Update AGESA 1.0.0.A.

F05

1. Optimize SMBIOS compatibility.
2. Optimize PCIe LAN card compatibility.
3. Optimize system inventory compatibility.

F04

1. Fixed CMT4032 could detect device.
2. Fixed BIOS Recovery
3. Update Inventory v04.
4. Support Auto bifurcation.
5. Update NVME WebUI information.
6. Support G493-ZB0 system sku.
7. Modify BIOS Item Default.

F03

1. First release MZB3-G43.
 2. Update AGESA 1.0.0.9.
-