

BIOS Release Notes

TITLE

SUBJECT: MZ33-DC0 BIOS Release Notes version F18
System: R263-Z33-AAF1-000,R263-Z33-AAL1-000,R263-Z35-AAF1-000,
R263-Z35-AAL1-000

About This Release

Build Date: 2024/05/15
BIOS Checksum: 0xBE65408F (32M)
Release Owner: Auto.Build(Ray.Xu)

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZ33-DC0-000
PCB Version:
Microcode updates versions:

CPUID	Family	Microcode Update ID
Genoa B0	Family 19h Model 10-1Fh	0x0A101020
Genoa B1	Family 19h Model 10-1Fh	0x0A101144
Genoa B2	Family 19h Model 10-1Fh	0x0A101244
Bergamo A0	Family 19h Model 10-1Fh	0x0AA00009
Bergamo A1	Family 19h Model 10-1Fh	0x0AA00116
Bergamo A2	Family 19h Model 10-1Fh	0x0AA00213

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT024
AGESA PI version: GenoaPI 1.0.0.B
OPROM version:

OPROM	Version
AST2600	1.12.00

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZ33-DC0_F18.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update

BIOS Release Notes

5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\Win32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\Win64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F18

1. Optimize AC Loss feature. (In Redfish function: only support command "PowerRestorePolicy")

F17

1. Enhance PCIe compatibility.

F16

1. Optimize Redfish compatibility.

F15

1. Update GBT Channel Genoa AGESA 1.0.0.B.
2. Support Endless Retry PXE feature.
3. Secure update: CVE-2023-31346, CVE-2023-31347, CVE-2023-39538, CVE-2023-39539, CVE-2023-45229, CVE-2023-45230, CVE-2023-45231, CVE-2023-45232, CVE-2023-45233, CVE-2023-45234, CVE-2023-45235.

F13

1. Optimize default year 2024.
2. Fixed X710 LAN Mac issue in Legacy mode.

BIOS Release Notes

F12

1. Fixed yellow bang in windows.
2. Fixed Redfish item fail issue.
3. Enhance Redfish feature.
4. Enhance NVMe hotplug feature.
5. Added Power btn control item.
6. Optimize SMBIOS compatibility.
7. Update AGESA 1.0.0.A.

F11

1. Optimize SMBIOS compatibility.
2. Optimize PCIe LAN card compatibility.
3. Optimize system inventory compatibility.

F10

1. Update AGESA 1.0.0.9.
2. Fixed system full DIMM reboot issue.
3. Fixed BIOS recovery issue.
4. Optimize SMBIOS compatibility.
5. Update System Inventory information v56.

F09

1. Fixed system reboot when error hold on.
2. Fixed yellow bang in windows.
3. Update AGESA 1.0.0.8.

F08

1. Adjusted BMC Watch Dog timer.
2. Optimize Chelsio cards compatibility.
3. Update AGESA 1.0.0.7.

F07

1. Update Inventory Mapping system.
2. Fixed COM Port mouse is not working.
3. Added DIMM Manufacturer ID 0x1A08.
4. Fixed NVME LED control failed.
5. Fixed SATA LED Control failed.
6. Adjust the display order of NVME devices list.
7. Added R263-Z35-AAF1-000, R263-Z35-AAL1-000 systems support.

BIOS Release Notes

F06

1. Updated AGESA 1.0.0.5.

F05

1. Added system R263-Z33-AAF1-000, R263-Z33-AAL1-000 support.
-