

G293-S40-AAP1

HPC/AI Server - 2U DP 8 x PCIe Gen4 GPUs

 **NVIDIA**
Certified



Features

- NVIDIA-Certified Systems™ - Data Center Servers
- Supports up to 8 x Dual slot Gen4 GPUs
- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- 8-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 4 x 2.5" Gen5 NVMe/SATA/SAS hot-swappable bays
- 4 x 2.5" SATA/SAS hot-swappable bays
- 8 x FHFL PCIe Gen4 x16 slots for GPUs
- 2 x LP PCIe Gen5 x16 slots for add-in cards
- Dual 3000W 80 PLUS Titanium redundant power supply

Specification

Dimensions	2U (W448 x H87.5 x D800 mm)	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
Motherboard	MS43-G20	Power Supply	Dual 3000W 80 PLUS Titanium redundant power supply AC Input: 100-240V
CPU	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors CPU TDP up to 225W	System Management	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Socket	2 x LGA 4677 (Socket E)	OS Compatibility	Windows Server 2019 / 2022 RHEL 8.6 / 8.7 / 8.8 / 8.9 / 8.10 / 9.0 / 9.1 / 9.2 / 9.3 / 9.4 SLES 15 SP4 / SP5 / SP6 Ubuntu 22.04 / 22.04.1 / 22.04.2 / 22.04.3 / 22.04.4 / 24.04 LTS VMware ESXi 7.0 Update 3o / 8.0 Update 1, Update 2, Update 3 Citrix Hypervisor 8.2 LTSR CU1
Chipset	Intel® C741 Chipset	System Fans	8 x 80x80x38mm (18,300rpm)
Memory	8-Channel DDR5 memory, 24 x DIMM slots RDIMM up to 96GB supported 3DS RDIMM modules up to 256GB supported Memory speed: Up to 5600 MT/s (1DPC), 4400 MT/s (2DPC)	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
LAN	2 x 10Gb/s LAN ports (1 x Intel® X710-AT2) Supported NCSI function 1 x 10/100/1000 management LAN	Packaging Content	1 x G293-S40-AAP1 2 x CPU heatsinks 6 x Carrier clips 8 x GPU power cables (12VHPWR, 250mm) 1 x L-shape Rail kit Packaging Dimensions: 1133 x 724 x 261 mm
Video	ASPEED® AST2600 Integrated 2D Graphic Adapter	Reference Numbers	Barebone with rail kit: 6NG293S40DR000AAP1* - L-shape Rail kit: 25HB2-A86102-K0R - CPU heatsink: 25ST1-35320F-C1R/25ST1-453207-C1R - Power supply: 25EP0-230005-G1S - C19 power cord 125V/15A (US): 25CP1-018000-Q0R (optional) - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R (optional) - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R (optional) - RMA packaging: 6NG293S40SR-RMA-A100 (optional)
Storage	4 x 2.5" Gen5 NVMe/SATA/SAS hot-swappable bays 4 x 2.5" SATA/SAS hot-swappable bays *SAS card is required to support SAS drives.		
RAID	Intel® SATA RAID 0/1/10/5 Support optional RAID add-in cards		
Expansion Slots	8 x PCIe Gen4 x16 FHFL slots for GPUs 2 x PCIe Gen5 x16 low-profile slots		
Internal I/O	1 x TPM header, 1 x VROC connector		
Rear I/O	2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN		
Backplane I/O	PCIe Gen5 x4 or SATA 6Gb/s or SAS 12Gb/s		



Learn more about GIGABYTE server at <https://www.gigabyte.com/Enterprise>

Designed by



* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* NVIDIA and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.