

# G4L3-ZD1-LAX3

HPC/AI Server - 4U DP HGX™ H200 8-GPU DLC



## Features

- Liquid-cooled NVIDIA HGX™ H200 8-GPU
- CPU+GPU direct liquid cooling solution with leak detection
- 900GB/s GPU-to-GPU bandwidth with NVLink® and NVSwitch™
- Dual AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- Compatible with NVIDIA BlueField®-3 DPUs and ConnectX®-7 NICs
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen3 x4 and x1 interface
- 8 x 2.5" Gen5 NVMe hot-swap bays
- 4 x FHHL dual-slot PCIe Gen5 x16 slots
- 8 x FHHL single-slot PCIe Gen5 x16 slots
- 4+4 3000W 80 PLUS Titanium redundant power supplies

## Specification

<b>Dimensions</b>	4U (W447 x H175.3 x D900 mm)	<b>I/O Ports</b>	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) Rear: 1 x MLAN
<b>Motherboard</b>	MSB3-PE0	<b>Backplane Board</b>	Speed and bandwidth: PCIe Gen5 x4
<b>Modular GPU</b>	Liquid-cooled NVIDIA HGX™ H200 with 8 x SXM GPUs	<b>TPM</b>	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM010
<b>CPU</b>	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Dual processor, cTDP up to 500W	<b>Power Supply</b>	4+4 3000W 80 PLUS Titanium redundant power supplies AC Input: 115-240V *The system power supply requires C19 power cord.
<b>Socket</b>	2 x LGA 6096 (Socket SP5)	<b>System Management</b>	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
<b>Chipset</b>	System on Chip	<b>OS Support</b>	Windows Server, Red Hat Enterprise Linux Server, VMware ESXi, SUSE Linux Enterprise, Ubuntu Server, Citrix Hypervisor
<b>Memory</b>	12-Channel DDR5 RDIMM, 24 x DIMMs [EPYC 9005] Up to 6000 MT/s [EPYC 9004] Up to 4800 MT/s	<b>System Fans</b>	Motherboard: 2 x 60x60x56mm, 2 x 60x60x76mm PCIe slots: 4 x 80x80x56mm (15,500rpm) GPU tray: 4 x 60x60x38mm (24,000rpm)
<b>LAN</b>	2 x 10Gb/s LAN ports (1 x Intel® X710-AT2) - Support NCSI function 1 x 10/100/1000 management LAN	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Video</b>	Integrated in ASPEED® AST2600 - 1 x VGA port	<b>Packaging Content</b>	1 x G4L3-ZD1-LAX3, 1 x CPU cold plate loop, 1 x L-shape Rail kit
<b>Storage</b>	Front hot-swap: 8 x 2.5" Gen5 NVMe Internal M.2: 1 x M.2 (2280/22110), PCIe Gen3 x4 1 x M.2 (2280/22110), PCIe Gen3 x1	<b>Part Numbers</b>	Barebone w/ NVIDIA module: 6NG4L3ZD1DR000LCX3*
<b>RAID</b>	Require RAID add-in cards		
<b>Expansion Slots</b>	4 x FHHL dual-slot PCIe Gen5 x16 slots 8 x FHHL single-slot PCIe Gen5 x16 slots		



Learn more at <https://www.GIGABYTE.com/enterprise>

Designed by



\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.  
\* NVIDIA, the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.