

# G593-ZD1-LAX3

HPC Server - 5U DP NVIDIA HGX™ H200 8-GPU



## Features

- CPU+GPU Direct liquid cooling solution
- 5U server system with NVIDIA HGX™ H200 8-GPU
- 900GB/s GPU-to-GPU bandwidth with NVLink® and NVSwitch™
- Dual AMD EPYC™ 9004 Series Processors
- 12-Channel RDIMM DDR5, 24 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen3 x4 and x1 interface
- 8 x 2.5" Gen5 NVMe hot-swappable bays
- 4 x FHHL PCIe Gen5 x16 slots
- 8 x LP PCIe Gen5 x16 slots
- 4+2 3000W 80 PLUS Titanium redundant power supplies

## Specification

<b>Dimensions</b>	5U (W447 x H219.7 x D945 mm)	<b>Application</b>	AI, AI Inference, AI Training, High-Performance Computing...
<b>Motherboard</b>	MZB3-G43	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>GPU</b>	Liquid cooled NVIDIA HGX™ H200 8-GPU (8-root ports)	<b>Backplane Board</b>	Speed and bandwidth: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
<b>CPU</b>	AMD EPYC™ 9004 Series processors Dual processor, 5nm technology cTDP up to 400W	<b>Power Supply</b>	4+2 3000W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
<b>Socket</b>	2 x LGA 6096 (Socket SP5)	<b>System Management</b>	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
<b>Chipset</b>	System on Chip	<b>OS Compatibility</b>	Windows Server, Red Hat Enterprise Linux Server, VMware ESXi, SUSE Linux Enterprise, Ubuntu Server, Citrix Hypervisor
<b>Memory</b>	24 x DIMM slots, 12-Channel DDR5 memory RDIMM up to 96GB; 3DS RDIMM up to 256GB supported Memory speed: Up to 4800 MT/s	<b>System Fans</b>	4 x 40x40x56mm (32,000rpm), 3 x 60x60x56mm (24,000rpm), 4 x 40x40x28mm (25,000rpm), 4 x 80x80x80mm (17,000rpm)
<b>LAN</b>	2 x 10Gb/s LAN ports (1 x Intel® X710-AT2) - Support NCSI function 1 x 10/100/1000 management LAN	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Video</b>	Integrated in ASPEED® AST2600 - 1 x VGA port	<b>Packaging Content</b>	1 x G593-ZD2-LAX3, 1 x CoolIT CPU cold plate loop, 1 x L-shape Rail kit Packaging Dimensions: 1200 x 890 x 700 mm
<b>Storage</b>	8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swappable bays *Storage card is required to support SATA and SAS drives. 1 x M.2 slot: M-key, PCIe Gen3 x4, supports 2280/22110 cards 1 x M.2 slot: M-key, PCIe Gen3 x1, supports 2280/22110 cards	<b>Part Numbers</b>	Barebone w/ NVIDIA module: 6NG593ZD1DR000LAX3*  Optional parts: - C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R
<b>Expansion Slots</b>	8 x PCIe Gen5 x16 low-profile slots 4 x PCIe Gen5 x16 FHHL slots		
<b>I/O ports</b>	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) Rear: 1 x MLAN Internal: 1 x TPM header		



Learn more at <https://www.GIGABYTE.com/enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.  
\* NVIDIA, the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

