

G493-SB4-AAP1

HPC/AI Server - 5th/4th Gen Intel® Xeon® Scalable - 4U DP NVIDIA OVX™ 8 x PCIe Gen5 GPUs



Key Features

- **NVIDIA-Certified Systems™ - OVX Servers**
- Optimized for NVIDIA OVX™ L40S Server with 8 GPUs configuration
- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 32 x DIMMs
- 2 x 10 Gb/s LAN ports via Intel® X710-AT2
- 12 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 1 x M.2 PCIe Gen3 x1
- 8 x FHFL PCIe Gen5 x16 for GPUs
- 2 x FHHL PCIe Gen5 x16
- 4 x LP PCIe Gen5 x16
- 1 x LP PCIe Gen4 x16 on the front side
- 3+1 3000 W 80 PLUS Titanium redundant power supplies

Specification

Dimensions	4U (W447 x H176 x D880 mm)	PCIe Expansion Slots	Rear: 8 x FHFL PCIe Gen5 x16, for GPUs 2 x FHHL PCIe Gen5 x16 4 x LP PCIe Gen5 x16 Front: 1 x LP PCIe Gen4 x16
Motherboard	MSB3-G40	I/O Ports	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN
CPU	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350 W	Backplane Board	PCIe Gen5 x4 or SATA 6 Gb/s or SAS-4 24 Gb/s
OS Compatibility	OS Support List	TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM010
Socket	2 x LGA 4677 (Socket E)	Power Supply	3+1 3000 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V *The system power supply requires C19 power cord.
Chipset	Intel® C741	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	8-Channel DDR5 RDIMM, 32 x DIMMs [5th Gen Intel Xeon] Up to 5600 MT/s (1DPC), 4400 MT/s (2DPC) [1] [4th Gen Intel Xeon] Up to 4800 MT/s (1DPC), 4400 MT/s (2DPC) [Intel Xeon Max Series] Up to 4800 MT/s (1DPC), 4400 MT/s (2DPC) [1] 5600 MT/s support under 2DPC configuration requires verified memory and BIOS setup.	System Fans	12 x 60x60x38mm [1] [1] Two fans share a single power connector.
LAN	2 x 10 Gb/s LAN ports (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Packaging Content	1 x G493-SB4-AAP1 2 x CPU fansinks 8 x GPU power cables (16-pin, 150mm) 6 x Carriers 1 x L-shape Rail kit
Storage	Front hot-swap: 12 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 [1] Internal M.2: 1 x M.2 (2280/22110), PCIe Gen3 x1 [1] SAS card is required to support SAS drives.	Ordering Part Numbers	6NG493SB4DR000ABP1*
RAID	Intel® SATA RAID 0/1/10/5 Onboard VROC key header Support optional RAID add-in cards		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Apr 27, 2026

Designed by

