


G494-SB4-AAP2

HPC/AI Server - Intel® Xeon® 6 - 4U DP 8 x PCIe Gen5 GPUs



Key Features

- Supports up to 8 x Dual slot Gen5 GPUs
- **Conditionally** supports
 - 8 x NVIDIA H200 NVL PCIe GPUs with 4-way NVLink bridges or
 - 8 x NVIDIA RTX PRO™ 6000 Blackwell Server Edition GPUs
- Dual Intel® Xeon® 6700/6500-Series Processors
- 8-Channel DDR5 RDIMM / MRDIMM, 32 x DIMMs
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 12 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 8 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x FHHL PCIe Gen5 x16 slots
- 3 x LP PCIe Gen5 x16 slots
- 2 x FHHL PCIe Gen5 x16 slots on the front side
- Quad 3000W 80 PLUS Titanium redundant power supply

Specification

Dimensions	4U (W448 x H176 x D880 mm) (W448 x H176 x D1000.5 mm with optional fan kit)
Motherboard	MSB4-G40
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors - Intel® Xeon® 6500-Series Processors Dual processor, TDP up to 350W
OS Compatibility	OS Support List
Socket	2 x LGA 4710 (Socket E2)
Chipset	System on Chip
Memory	8-Channel DDR5 RDIMM/MRDIMM, 32 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s ^[1] ^[1] MRDIMMs are supported only on select Intel® Xeon® 6 processors with P-cores and only in a 1DPC configuration.
LAN	2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN
Video	Integrated in ASPEED® AST2600 - 1 x VGA port
Storage	Front hot-swap: 12 x 2.5" Gen5 NVMe/SATA/SAS-4 ^[1] ^[1] Storage card is required to support SATA and SAS drives.
RAID	Require RAID add-in cards Onboard VROC key headers

PCIe Expansion Slots	Rear: 8 x FHFL PCIe Gen5 x16, for GPUs 2 x FHHL PCIe Gen5 x16 3 x LP PCIe Gen5 x16 Front: 2 x FHHL PCIe Gen5 x16 *The system supports up to 8 x 600W GPUs with an optional fan kit. GPU video output ports are not available. *The system supports 8 x NVIDIA H200 NVL PCIe GPUs at 25°C ambient, arranged as two 4-GPU sets, each with a 4-way NVLink bridge. *The system supports 8 x RTX PRO™ 6000 Blackwell Server Edition GPUs at 25°C ambient.
I/O Ports	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN
Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM012 1 x PROt connector (only enabled on RoT SKU)
Power Supply	Quad 3000W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
System Fans	2 x 40x40x28mm 12 x 60x60x56mm
Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Packaging Content	1 x G494-SB4-AAP2 2 x CPU fansinks 8 x GPU power cables (16-pin, 150mm) 4 x Carriers 1 x L-shape Rail kit
Ordering Part Numbers	6NG494SB4DR000AAP2*
Optional Parts	- 8080 fan kit for 600W GPUs: 6NG494SB0S0000AAP2* (packaging dimensions: L441 x W242 x H272 mm)



Learn more at: <https://www.gigabyte.com/Enterprise>
* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.
Last updated: Jan 21, 2026