

G593-SD1-LAX3

HPC/AI Server - 5th/4th Gen Intel® Xeon® Scalable - 5U DP NVIDIA HGX™ H200 DLC



Key Features

- NVIDIA-Certified Systems™ - Data Center Servers
- Liquid-cooled NVIDIA HGX™ H200
- CPU+GPU direct liquid cooling solution
- 900GB/s GPU-to-GPU bandwidth with NVIDIA NVLink™ and NVSwitch™
- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 32 x DIMMs
- Compatible with NVIDIA® BlueField®-3 DPUs/SuperNICs
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 4 x FHH PCIe Gen5 x16 slots
- 8 x LP PCIe Gen5 x16 slots
- 4+2 3000W 80 PLUS Titanium redundant power supplies

Specification

Dimensions	5U (W447 x H219.7 x D945 mm)	Modular GPU	Liquid-cooled NVIDIA HGX™ H200 with 8 x SXM GPUs
Motherboard	MSB3-G41	PCIe Expansion Slots	4 x FHH PCIe Gen5 x16 8 x LP PCIe Gen5 x16
CPU	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350W	I/O Ports	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) Rear: 1 x MLAN
OS Compatibility	OS Support List	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Socket	2 x LGA 4677 (Socket E)	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Chipset	Intel® C741	Power Supply	4+2 3000W 80 PLUS Titanium redundant power supplies AC Input: 115-240V
Memory	8-Channel DDR5 RDIMM, 32 x DIMMs [5th Gen Intel Xeon] Up to 5600 MT/s (1DPC), 4400 MT/s (2DPC) ^[1] [4th Gen Intel Xeon] Up to 4800 MT/s (1DPC), 4400 MT/s (2DPC) [Intel Xeon Max Series] Up to 4800 MT/s (1DPC), 4400 MT/s (2DPC)	System Fans	Motherboard: 2 x 40x40x28mm / 3 x 60x60x56mm PCIe slots: 4 x 40x40x28mm / 2 x 40x40x56mm GPU tray: 4 x 80x80x80mm
	^[1] 5600 MT/s support under 2DPC configuration requires verified memory and BIOS setup.	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	Front: 2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN Rear: 1 x 10/100/1000 Mbps Management LAN		*To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 45°C.
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Packaging Content	1 x G593-SD1-LAX3 6 x Carriers 1 x L-shape Rail kit
Storage	Front hot-swap: 8 x 2.5" Gen5 NVMe/SATA/SAS-4 ^[1] ^[1] SAS card is required to support SAS drives.	Ordering Part Numbers	6NG593SD1DR000LBX3*
RAID	Intel® SATA RAID 0/1/10/5 Support optional RAID add-in cards		

Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Jan 27, 2026

Designed by

