

H233-Z80-AAW1 (Rev. 1.x)

High Density Server - AMD EPYC™ 9004 Server Processors -
2U 2-Node DP, 4 x PCIe Gen5 GPUs, 3000 W



Key Features

- Supports up to 4 x dual-slot PCIe Gen5 GPUs
- 2U 2-node rear access server system
- Dual AMD EPYC™ 9004 Server processors per node
- 12-Channel DDR5 RDIMM per CPU with 24 x DIMMs per node
- 4 x 1 Gb/s LAN ports via Intel® I350-AM2
- 4 x 2.5" Gen4 NVMe hot-swap bays
- 4 x FHFL PCIe x16 slots with Gen5 x16 lanes for GPUs
- 2 x LP PCIe x16 slots with Gen5 x16 lanes
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 3000 W 80 PLUS Titanium redundant power supplies

Applications

AI Platform, AI Training Server, AI Inference Server, High-Performance Computing Server, High Converged Server, Servers for Hybrid/Private Cloud...

Specification

Dimensions	2U 2-Node - Rear access (W440 x H87.5 x D877 mm)	I/O Ports	Front: 1 x CMC status LED, 1 x CMC reset button Rear: 4 x USB 3.2 Gen1, 2 x Mini-DP, 4 x RJ45, 2 x MLAN
Motherboard	MZ83-HD0	Backplane Board	PCIe Gen4 x4
CPU	AMD EPYC™ 9005 Server processors AMD EPYC™ 9004 Server processors Dual processors per node, cTDP up to 240 W	TPM	2 x TPM headers (SPI), Optional TPM 2.0 kit: CTM010
OS Compatibility	OS Support List	Power Supply	Dual 3000 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V *The system power supply requires C19 power cord.
Socket	4 x LGA 6096 (Socket SP5)	System Management	ASPEED® AST2600 Baseboard Management Controller ASPEED® AST2520 Chassis Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	System Fans	4 x 80x80x80mm
Memory	12-Channel DDR5 RDIMM, 48 x DIMMs Up to 4800 MT/s	Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	4 x 1 Gb/s LAN (2 x Intel® I350-AM2), Support NCSI 2 x 10/100/1000 Mb/s Management LAN	Packaging Content	1 x H233-Z80-AAW1 4 x CPU heatsinks 1 x Mini-DP to D-Sub cable 4 x GPU power cables (CPU 8pin, 400 mm) 1 x 3-Section Rail kit
Video	Integrated in ASPEED® AST2600 x 2 - 2 x Mini-DP	Ordering Part Numbers	6NH233Z80DR000ABW1*
Storage	Front hot-swap: 4 x 2.5" Gen4 NVMe		
RAID	Require RAID add-in cards		
PCIe Expansion Slots	4 x FHFL x16 (Gen5 x16), for GPUs 2 x LP x16 (Gen5 x16) 2 x OCP NIC 3.0 (Gen5 x16), Support NCSI		



Learn more at: <https://www.gigabyte.com/Enterprise>
* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.
Last updated: Sep 7, 2026

Designed by

