

# H262-Z6A (Rev. 100)

High Density Server - AMD EPYC™ 7002/7001 -  
2U 4-Node DP 24-Bay Gen4 NVMe/SATA/SAS



## Key Features

- Hardware-level root of trust support
- 2U 4-node rear access server system
- Dual AMD EPYC™ 7002/7001 Series Processors per node
- 8-Channel DDR4 RDIMM/LRDIMM, 16 x DIMMs per node
- 8 x 1 Gb/s LAN ports via Intel® I350-AM2
- 1 x CMC port
- 24 x 2.5" Gen4 NVMe/SATA/SAS hot-swap bays
- 4 x M.2 slots with PCIe Gen4 x4 interface
- 8 x LP PCIe Gen4 x16 slots
- 4 x OCP NIC 3.0 PCIe Gen4 x16 slots
- Dual 2200 W 80 PLUS Platinum redundant power supplies

## Applications

High Converged Server, Servers for Hybrid/Private Cloud...

## Specification

<b>Dimensions</b>	2U 4-Node - Rear access (W440 x H87.5 x D840 mm)
<b>Motherboard</b>	MZ62-HD4
<b>CPU</b>	AMD EPYC™ 7002 Series Processors AMD EPYC™ 7001 Series Processors Dual processor per node, TDP up to 200 W  *Contact our sales representatives or technical support for more details about supporting cTDP 240 W CPUs.
<b>Socket</b>	8 x LGA 4094 (Socket SP3)
<b>Chipset</b>	System on Chip
<b>Memory</b>	8-Channel DDR4 RDIMM/LRDIMM, 64 x DIMMs Up to 3200 MT/s
<b>LAN</b>	8 x 1 Gb/s LAN (4 x Intel® I350-AM2), Support NCSI 4 x 10/100/1000 Mb/s Management LAN 1 x CMC port
<b>Video</b>	Integrated in ASPEED® AST2500 x 4 - 4 x Mini-DP
<b>Storage</b>	<b>Front hot-swap:</b> 24 x 2.5" Gen4 NVMe/SATA/SAS [1] <b>Internal M.2:</b> 4 x M.2 (2280/22110), PCIe Gen4 x4  [1] SAS card is required to support SAS drives.
<b>RAID</b>	Require RAID add-in cards
<b>PCIe Expansion Slots</b>	8 x LP x16 (Gen4 x16) 4 x OCP NIC 3.0 (Gen4 x16), Support NCSI

<b>I/O Ports</b>	<b>Front:</b> 1 x CMC status LED, 1 x CMC reset button <b>Rear:</b> 8 x USB 3.0, 4 x Mini-DP, 8 x RJ45, 4 x MLAN, 1 x CMC port
<b>Backplane Board</b>	PCIe Gen4 x4 or SATA 6 Gb/s or SAS 12 Gb/s
<b>TPM</b>	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM010
<b>Power Supply</b>	Dual 2200 W 80 PLUS Platinum redundant power supplies AC Input: 100-240 V  *The system power supply requires C19 power cord.
<b>System Management</b>	ASPEED® AST2500 Baseboard Management Controller ASPEED® AST2520 Chassis Management Controller GIGABYTE Management Console web interface
<b>System Fans</b>	8 x 80x80x38mm
<b>Operating Properties</b>	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
<b>Packaging Content</b>	1 x H262-Z6A 8 x CPU heatsinks 1 x 3-Section Rail kit
<b>Ordering Part Numbers</b>	6NH262Z6AMR-00-1*
<b>Optional Parts</b>	- C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - M.2 expansion card - CMTP061: 9CMTP061NR-00* - Ring topology kit: 6NH262Z65SR-00-100 - Mini-DP to D-Sub cable: 25CRN-200801-K1R



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: May 25, 2026

Designed by

