



H273-Z80-LAN1 (Rev. 3.x)

High Density Server - AMD EPYC™ 9005/9004 -
2U 4-Node DP 24-Bay Gen4 NVMe/SATA/SAS 2600W DLC



Key Features

- Direct liquid cooling solution
- 2U 4-node rear access server system
- Dual AMD EPYC™ 9005/9004 Series Processors per node
- 12-Channel DDR5 RDIMM, 24 x DIMMs per node
- 8 x 1Gb/s LAN ports via Intel® I350-AM2
- 24 x 2.5" Gen4 NVMe/SATA/SAS hot-swap bays
- 4 x M.2 slots with PCIe Gen4 x4 interface **(optional)**
- 4 x LP PCIe Gen5 x16 slots
- 4 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 2600W 80 PLUS Titanium redundant power supply

Applications

High-Performance Computing Server, High Converged Server...

Specification

Dimensions	2U 4-Node - Rear access (W440 x H87.5 x D877 mm)
Motherboard	MZ83-HD0
CPU	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Dual processor per node, cTDP up to 400W
OS Compatibility	OS Support List
Socket	8 x LGA 6096 (Socket SP5)
Chipset	System on Chip
Memory	12-Channel DDR5 RDIMM, 96 x DIMMs [EPYC 9005] Up to 6400 MT/s [EPYC 9004] Up to 4800 MT/s
LAN	8 x 1Gb/s LAN (4 x Intel® I350-AM2), Support NCSI 4 x 10/100/1000 Mbps Management LAN
Video	Integrated in ASPEED® AST2600 x 4 - 4 x Mini-DP
Storage	Front hot-swap: 24 x 2.5" Gen4 NVMe/SATA/SAS ^[1] Optional internal M.2: 4 x M.2 (2280/22110), PCIe Gen4 x4 ^[1] SAS card is required to support SAS drives.
RAID	Require RAID add-in cards

PCIe Expansion Slots	4 x LP PCIe Gen5 x16 4 x OCP NIC 3.0 PCIe Gen5 x16, Support NCSI
I/O Ports	Front: 1 x CMC status LED, 1 x CMC reset button Rear: 8 x USB 3.2 Gen1, 4 x Mini-DP, 8 x RJ45, 4 x MLAN
Backplane Board	PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Power Supply	Dual 2600W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
System Fans	4 x 80x80x38mm (18,300rpm)
Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing) *To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 45°C.
Packaging Content	1 x H273-Z80-LAN1 4 x CoolIT CPU cold plate loops 1 x Mini-DP to D-Sub cable 1 x 3-Section Rail kit
Ordering Part Numbers	6NH273Z80DR000LCN1*
Optional Parts	- M.2 expansion card - CMTP192: 9CMTP192NR-00* - GIGABYTE CPU cold plate loop: 25H27-3Z80000-E06X (QPA:4) - GIGABYTE 2U4N manifold: 25H27-3Z80000-E07X (1 set per rack) - CoolIT leak sensor board: 6NH273Z80S1000LAN11 (QPA: 4)



Learn more at: <https://www.gigabyte.com/Enterprise>
* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.
Last updated: Jan 27, 2026