


ME03-PE0 (Rev. 1.x/3.x)

Motherboard - AMD EPYC™ 8005/8004 Server Processors - ATX UP



Key Features

- Single AMD EPYC™ 8005/8004 Server Processors
- 6-Channel DDR5 RDIMM per CPU with 6 x DIMMs
- 2 x 1 Gb/s LAN ports via Broadcom® BCM5720
- 2 x MCIO 8i connectors supporting PCIe Gen5 x8
- 1 x M.2 slot with PCIe Gen3 x4
- 3 x PCIe x16 slots with Gen5 x16 lanes
- 4 x PCIe x16 slots with Gen4 x16 and x8 lanes

Specification

Form Factor	ATX (W304.8 x D243.8 mm)	Internal I/O	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header / 5 x System fan headers 1 x USB 3.2 Gen1 x2 header / 1 x M.2 slot 2 x MCIO 8i connectors / 1 x Front panel header 1 x Backplane board header / 1 x PMBus connector 1 x IPMB connector / 1 x TPM header
CPU	AMD EPYC™ 8005 Server Processors AMD EPYC™ 8004 Server Processors Single processor, cTDP up to 225 W	Rear I/O	2 x USB 3.2 Gen1 ports (Type-A) 1 x VGA port 1 x Serial port 2 x RJ45 ports 1 x MLAN port 1 x ID button with LED
Socket	1 x LGA 4844 (Socket SP6)	Security Modules	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM010
Chipset	System on Chip	Board Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	6-Channel DDR5 RDIMM, 6 x DIMMs [EPYC 8005] Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC) [EPYC 8004] Up to 4800 MT/s (1DPC), 3600 MT/s (2DPC)	PSU Connectors	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors
OS Compatibility	OS Support List	Operating Properties	Operating: 10°C to 40°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	2 x 1 Gb/s LAN (1 x Broadcom® BCM5720), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Retail Packaging Content	1 x ME03-PE0 1 x I/O shield 1 x Quick start guide 1 x MCIO 8i to 8 x SATA cable (600mm) Quantity: 10 x single boxes in one carton
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Bulk Packaging Content	10 x ME03-PE0 10 x I/O shields
Audio	N/A	Ordering Part Numbers	Retail: 9ME03PE0MR-000-3* Bulk: 9ME03PE0NR-000-3*
Storage Interface	MCIO: 2 x MCIO 8i for 4 x Gen5 NVMe or 16 x SATA M.2: 1 x M.2 (2280/22110), PCIe Gen3 x4	Optional Parts	- MCIO 8i to 2 x MCIO 4i cable (550mm); 25CF9-550700-A4R
RAID	N/A		
PCIe Expansion Slots	Slot_7: PCIe x16 (Gen5 x16) Slot_6: PCIe x16 (Gen5 x16) Slot_5: PCIe x16 (Gen5 x16) Slot_4: PCIe x16 (Gen4 x0 or x8), shared with Slot_3 Slot_3: PCIe x16 (Gen4 x16 or x8), shared with Slot_4 Slot_2: PCIe x16 (Gen4 x0 or x8), shared with Slot_1 Slot_1: PCIe x16 (Gen4 x16 or x8), shared with Slot_2 2 x MCIO 8i (Gen5 x8 or SATA)		



Learn more at: <https://www.gigabyte.com/Enterprise>
* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.
Last updated: Jul 20, 2026

Designed by

