

# MS73-HB0 (Rev. 1.x/3.x)

Motherboard - 5th/4th Gen Intel® Xeon® Scalable - E-ATX DP 10Gb/s Intel Ethernet Controller



## Key Features

- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 16 x DIMMs
- Intel® C741 Chipset
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x 1Gb/s LAN ports via Intel® I210-AT
- 3 x SlimSAS 4i connectors with SATA interface
- 2 x SATA 7-pin ports
- 2 x M.2 slots with PCIe Gen4 x4 interface
- 6 x PCIe Gen5 x16 expansion slots

## Specification

<b>Form Factor</b>	E-ATX (W304.8 x D330.2 mm)	<b>Internal I/O</b>	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 2 x 6-pin ATX 12V power connectors 2 x CPU fan headers / 4 x System fan headers 1 x USB 3.2 Gen1 x2 header / 2 x M.2 slots 3 x SlimSAS 4i connectors / 2 x SATA 7-pin connectors 1 x VROC connector / 1 x Front panel header 1 x Backplane board header / 1 x PMBus header 1 x IPMB header / 1 x TPM header
<b>CPU</b>	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350W	<b>Rear I/O</b>	2 x USB 3.2 Gen1 ports (Type-A) 1 x VGA port 1 x RJ45 serial port 4 x RJ45 ports 1 x MLAN port 1 x ID button with LED
<b>Socket</b>	2 x LGA 4677	<b>Security Modules</b>	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
<b>Chipset</b>	Intel® C741	<b>PSU Connectors</b>	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 2 x 6-pin ATX 12V power connectors
<b>Memory</b>	8-Channel DDR5 RDIMM, 16 x DIMMs [5th Gen Intel Xeon] Up to 5600 MT/s [4th Gen Intel Xeon] Up to 4800 MT/s [Intel Xeon Max Series] Up to 4800 MT/s	<b>Operating Properties</b>	Operating: 10°C to 40°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
<b>OS Compatibility</b>	<a href="#">OS Support List</a>	<b>Retail Packaging Content</b>	1 x MS73-HB0 1 x I/O shield 1 x Quick start guide 6 x Carriers 1 x SlimSAS 4i to 4 x SATA cable (600mm)  Quantity: 10 x single boxes in one carton
<b>LAN</b>	2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 2 x 1Gb/s LAN (2 x Intel® I210-AT), Support NCSI 1 x 10/100/1000 Mbps Management LAN	<b>Bulk Packaging Content</b>	10 x MS73-HB0 10 x I/O shields 60 x Carriers
<b>Video</b>	Integrated in ASPEED® AST2600 - 1 x VGA port	<b>Ordering Part Numbers</b>	Retail: 9MS73HB0MR-000-3*/1* Bulk: 9MS73HB0NR-000-3*/1*
<b>Audio</b>	N/A	<b>Optional Parts</b>	- CPU fansink: 25ST0-0Z9221-A3R
<b>Storage Interface</b>	<b>SlimSAS:</b> 3 x SlimSAS 4i for 12 x SATA <b>SATA 7-pin:</b> 2 x SATA <b>M.2:</b> 2 x M.2 (2280/22110), PCIe Gen4 x4		
<b>RAID</b>	Intel® SATA RAID 0/1/10/5 Onboard VROC key header		
<b>PCIe Expansion Slots</b>	6 x PCIe Gen5 x16		



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Mar 23, 2026

Designed by