


MU72-SU0 (Rev. 1.x/2.x)

Motherboard - 3rd Gen Intel® Xeon® Scalable & Intel® Xeon® W-3300 - ATX, UP



Key Features

- Single 3rd Gen Intel® Xeon® Scalable processors or Intel® Xeon® W-3300 processors
- 8-Channel DDR4 RDIMM/LRDIMM per CPU with 8 x DIMMs
- Supports Intel® Optane™ Persistent Memory 200 series
- Intel® C621A Chipset
- 2 x 1 Gb/s LAN ports via Intel® I210-AT
- 3 x SlimSAS 4i connectors supporting SATA
- 1 x M.2 slot with PCIe Gen3 x4
- 7 x PCIe x16 slots with Gen4 x16 or x8 lanes

Specification

Form Factor	ATX (W304.8 x D244 mm)	Internal I/O	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x 6-pin ATX 12V power connector (for PCIe slots) 1 x CPU fan header / 6 x System fan headers 1 x USB 3.0 x2 header / 1 x M.2 slot 3 x SlimSAS 4i connectors / 1 x VROC connector 1 x Front panel header / 1 x Backplane board header 1 x PMBus header / 1 x IPMB header 1 x TPM header
CPU	3rd Generation Intel® Xeon® Scalable processors Intel® Xeon® W-3300 processors Single processor, TDP up to 270 W	Rear I/O	4 x USB 3.0 ports (Type-A) 1 x VGA port 1 x Serial port 2 x RJ45 ports 1 x MLAN port 1 x ID button with LED
Socket	1 x LGA 4189 (Socket P+)	Security Modules	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM010
Chipset	Intel® C621A	PSU Connectors	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x 6-pin ATX 12V power connector (for PCIe slots)
Memory	8-channel DDR4 RDIMM/LRDIMM, 8 x DIMMs Up to 3200/2933/2666 MT/s	Operating Properties	Operating: 10°C to 40°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	2 x 1 Gb/s LAN (2 x Intel® I210-AT), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Retail Packaging Content	1 x MU72-SU0 1 x I/O shield 1 x Quick start guide 1 x SlimSAS 4i to 4 x SATA cable (600 mm) Quantity: 10 x single boxes in one carton
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Bulk Packaging Content	10 x MU72-SU0 10 x I/O shields
Audio	N/A	Ordering Part Numbers	Retail: 9MU72SU0MR-00-2*/1* Bulk: 9MU72SU0NR-00-2*/1*
Storage Interface	SlimSAS: 3 x SlimSAS 4i for 12 x SATA, from PCH M.2: 1 x M.2 (2280), PCIe Gen3 x4	Optional Parts	- Fansink: 25ST4-353203-M1R
RAID	Intel® SATA RAID 0/1/10/5 Onboard VROC key header		
PCIe Expansion Slots	Slot_7: PCIe x16 (Gen4 x16) Slot_6: PCIe x16 (Gen4 x16 or x8), shared with Slot_5 Slot_5: PCIe x16 (Gen4 x8), shared with Slot_6 Slot_4: PCIe x16 (Gen4 x16 or x8), shared with Slot_3 Slot_3: PCIe x16 (Gen4 x8), shared with Slot_4 Slot_2: PCIe x16 (Gen4 x16 or x8), shared with Slot_1 Slot_1: PCIe x16 (Gen4 x8), shared with Slot_2		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Sep 29, 2026

Designed by

