

MW94-RP0 (Rev. 1.x)

Motherboard - Intel® Xeon® 600 Processors for Workstations - E-ATX UP



Key Features

- Single Intel® Xeon® 600 Processors for Workstations
- 8-Channel DDR5 RDIMM/MRDIMM, 8 x DIMMs
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x MCIO 8i connectors with PCIe Gen5 x8 interface*
- 1 x SlimSAS 8i connector with PCIe Gen4 x8 interface
- 2 x SlimSAS 4i connectors with SATA interface
- 4 x M.2 slots with PCIe Gen5 x4 interface
- 4 x PCIe Gen5 x16 expansion slots
- 2 x PCIe Gen5 x16 expansion slots*

* Require Intel® Xeon® 690/670/650 processors.

Specification

Form Factor	E-ATX (W304.8 x D330.2 mm)	Internal I/O	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x 4-pin power connector (for PCIe slots) 1 x CPU fan header 6 x System fan headers 1 x Front audio header 1 x USB 3.2 Gen2x2 header (Type-E) 1 x USB 3.2 Gen1 x2 header 4 x M.2 slots 2 x MCIO 8i connectors 1 x SlimSAS 8i connector 2 x SlimSAS 4i connectors 1 x VROC connector 1 x Front panel header 1 x Backplane board header 1 x PMBus header 1 x IPMB header 1 x TPM header
CPU	Intel® Xeon® 600 processors for workstations Single processor, TDP up to 350W *Please select Intel® Xeon® 690/670/650 processors to enable all functions.	Rear I/O	1 x USB 3.2 Gen2x2 port (Type-C) 3 x USB 3.2 Gen2x1 ports (Type-A) 1 x VGA port 1 x Serial port 2 x RJ45 ports 1 x MLAN port 3 x Audio jacks 1 x ID button with LED
Socket	1 x LGA 4710-2	Security Modules	1 x TPM header (SPI), Optional TPM2.0 kit: CTM012
Chipset	Intel® W890	Board Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	8-channel DDR5 RDIMM/MRDIMM, 8 x DIMMs [1] [RDIMM] Up to 6400 MT/s [MRDIMM] Up to 8000 MT/s [2] [1] Only 4 x DIMMs are supported with Intel® Xeon® 630 processors. [2] MRDIMMs are supported only on select SKUs.	PSU Connectors	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x 4-pin power connector (for PCIe slots)
LAN	2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C to 40°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Ordering Part Numbers	Retail: 9MW94RP0MR-000-1* Bulk: 9MW94RP0NR-000-1*
Audio	Realtek® ALC897 HD Audio Codec Supports 2/4/5.1/7.1 channel configurations 3 x Audio Jacks (Audio in/Audio out/Mic)		
Storage Interface	MCIO: 2 x MCIO 8i for 4 x Gen5 NVMe [1] SlimSAS: 1 x SlimSAS 8i for 2 x Gen4 NVMe 2 x SlimSAS 4i for 8 x SATA M.2: 4 x M.2 (2280/22110), PCIe Gen5 x4 [1] Require Intel® Xeon® 690/670/650 processors.		
RAID	Intel® SATA RAID 0/1/10/5 Onboard VROC key header		
PCIe Expansion Slots	4 x PCIe Gen5 x16 2 x PCIe Gen5 x16 [1] 2 x MCIO 8i (Gen5 x8) [1] Slot_2/6 require Intel® Xeon® 690/670/650 processors.		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Mar 10, 2026

Designed by

