

R185-D90-LS1

Rack Server - AMD EPYC™ 9006 SP7 Server Processors -
1U DP 4-Bay Gen5 NVMe/SATA/SAS-4 DLC



Key Features

- CPU direct liquid cooling solution with leak detection
- Dual AMD EPYC™ 9006 SP7 Server processors
- 16-Channel DDR5 RDIMM/MRDIMM per CPU with 32 x DIMMs
- 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 2 x M.2 slots with PCIe Gen4 x4
- 3 x LP PCIe x16 slots with Gen6 x16 lanes
- 1 x OCP NIC 3.0 PCIe Gen6 x16 slot
- 2 x 3200 W 80 PLUS Titanium redundant power supplies

Applications

Networks Server, Servers for Hybrid/Private Cloud...

Specification

Dimensions	1U (W438 x H43.5 x D815 mm)	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 1 x MLAN
Motherboard	MD95-FS0	TPM	2 x TPM headers (SPI), Optional TPM 2.0 kit: CTM012
CPU	AMD EPYC™ 9006 SP7 Server processors [DLC] Dual processors, PPT up to 600 W	Power Supply	2 x 3200 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V *The system power supply requires C19 power cord.
Socket	2 x LGA 7536 (Socket SP7)	System Fans	8 x 40x40x56mm
Chipset	Integrated into SoC	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing) *To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 45°C.
Memory	16-Channel DDR5 RDIMM/MRDIMM, 32 x DIMMs [RDIMM] Up to 8000 MT/s [MRDIMM] Up to 12800 MT/s [1] [1] MRDIMMs are supported only on select CPU SKUs.	Packaging Content	1 x R185-D90-LS1 1 x CPU cold plate loop 1 x Mini-DP to D-Sub cable 1 x 2-Section Rail kit
LAN	1 x Management LAN	Ordering Part Numbers	6NR185D90HR000LS1*
Video	Integrated in ASPEED® AST2700 - 1 x Mini-DP	Optional Parts	- 3-Section Rail kit (Supports CMA): 25HB2-A56121-K0R - Cable Management Arm: 25HB1-R18300-K0R
Storage	Front hot-swap: 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 [1] Internal M.2: 2 x M.2 (2242/2260/2280/22110), PCIe Gen4 x4 [1] Storage card is required to support SATA and SAS drives.		
PCIe Expansion Slots	3 x LP x16 (Gen6 x16) 1 x OCP NIC 3.0 (Gen6 x16), Support NCSI		

