

XV23-ZX0-AAJ1 (Rev. 3.x)

NVIDIA MGX™ Server - AMD EPYC™ 9005/9004 - 2U DP 4 x PCIe Gen5 GPUs



Key Features

- Supports up to 4 x Dual slot Gen5 GPUs
 - 4 x NVIDIA H200 NVL PCIe GPUs with 2-way NVLink bridges
 - 4 x NVIDIA RTX PRO™ 6000 Blackwell Server Edition
- NVIDIA MGX™ modular server design
- Dual AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- 2 x 10 Gb/s LAN ports via Intel® X550-AT2
- 6 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 3 x M.2 PCIe Gen3 x2 and x1
- 4 x FHFL PCIe Gen5 x16 for GPUs
- 3 x FHFL PCIe Gen5 x16
- 3+1 2000 W 80 PLUS Titanium redundant power supplies

Applications

AI Platform, AI Training Server, AI Inference Server, Visual Computing, High-Performance Computing Server...

Specification

Dimensions	2U (W438 x H87 x D900 mm)	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
Motherboard	MZX3-MG0	Backplane Board	PCIe Gen5 x4 or SATA 6 Gb/s or SAS-4 24 Gb/s
CPU	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Dual processor, cTDP up to 400 W - At 30°C ambient, cTDP up to 500 W	TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012
OS Compatibility	OS Support List	Power Supply	3+1 2000 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V
Socket	2 x LGA 6096 (Socket SP5)	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	System Fans	4 x 80x80x80mm
Memory	12-Channel DDR5 RDIMM, 24 x DIMMs [EPYC 9005] Up to 6400 MT/s [EPYC 9004] Up to 4800 MT/s	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	2 x 10 Gb/s LAN (1 x Intel® X550-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Packaging Content	1 x XV23-ZX0-AAJ1 2 x CPU heatsinks 1 x Mini-DP to D-Sub cable 2 x GPU power cables (16-pin, 620mm) 2 x GPU power cables (16-pin, 750mm) 1 x 3-Section Rail kit
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Ordering Part Numbers	6NXV23ZX0HR000ACJ1*
Storage	Front hot-swap: 6 x 2.5" Gen5 NVMe/SATA/SAS-4 ^[1] Internal M.2: 2 x M.2 (2280/22110), PCIe Gen3 x2 1 x M.2 (2280/22110), PCIe Gen3 x1 ^[1] Storage card is required to support SATA and SAS drives.	Optional Parts	- Chassis intrusion switch: 25HA1-R28390-U1R - Cable Management Arm: 25HB2-2AA700-K0R
PCIe Expansion Slots	4 x FHFL PCIe Gen5 x16, for GPUs 3 x FHFL PCIe Gen5 x16 *The system supports 4 x NVIDIA H200 NVL PCIe GPUs at 25°C ambient, arranged as two 2-GPU sets, each with a 2-way NVLink bridge. *The system supports 4 x RTX PRO™ 6000 Blackwell Server Edition GPUs at 25°C ambient. *The system is only validated with a uniform GPU model.		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Apr 7, 2026

Designed by

