

G295-D21-AP1

HPC/AI Server - AMD EPYC™ 9006 SP7 Server Processors -
2U UP 4 x PCIe Gen6 GPUs



Key Features

- Supports up to 4 x dual-slot Gen6 GPUs
- Single AMD EPYC™ 9006 SP7 Server processors
- 12-Channel DDR5 RDIMM/MRDIMM per CPU with 12 x DIMMs
- 2 x 10 Gb/s LAN ports via Broadcom® BCM57416
- 2 x 2.5" Gen5 NVMe hot-swap bays
- **Optional** 4 x 2.5" Gen5 NVMe/SATA/SAS-4 or 6 x 2.5" SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen4 x2
- 4 x FHFL PCIe x16 slots with Gen6 x16 lanes for GPUs
- 1 x LP PCIe x16 slot with Gen6 x16 lanes for add-in cards
- 1 x LP PCIe x16 slot with Gen6 x8 lanes for add-in cards
- 2 x 3000 W 80 PLUS Titanium redundant power supplies

Applications

AI Platform, AI Training Server, AI Inference Server, Visual Computing, High-Performance Computing Server...

Specification

Dimensions	2U (W448 x H87.5 x D800 mm)	PCIe Expansion Slots	4 x FHFL x16 (Gen6 x16), for GPUs 1 x LP x16 (Gen6 x16), for add-in cards 1 x LP x16 (Gen6 x8), for add-in cards
Motherboard	MD25-G20	I/O Ports	Rear: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN
CPU	AMD EPYC™ 9006 SP7 Server processors Single processor, PPT up to 600 W	TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012
Socket	1 x LGA 7536 (Socket SP7)	Power Supply	2 x 3000 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V *The system power supply requires C19 power cord.
Chipset	Integrated into SoC	System Fans	6 x 80x80x80mm
Memory	12-Channel DDR5 RDIMM/MRDIMM, 12 x DIMMs [RDIMM] Up to 8000 MT/s [MRDIMM] Up to 12800 MT/s ^[1] ^[1] MRDIMMs are supported only on select CPU SKUs.	Operating Properties	Operating: 10°C to 25°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
LAN	2 x 10 Gb/s LAN (1 x Broadcom® BCM57416), Support NCSI 1 x Management LAN	Packaging Content	1 x G295-D21-AP1 1 x CPU heatsink 3 x GPU power cables (16-pin, 250mm) 1 x GPU power cable (16-pin, 280mm) 1 x L-shape Rail kit
Video	Integrated in ASPEED® AST2700 - 1 x VGA port	Ordering Part Numbers	6NG295D21HR000AP1*
Storage	Front hot-swap: 2 x 2.5" Gen5 NVMe Optional front hot-swap: 4 x 2.5" Gen5 NVMe/SATA/SAS-4 or 6 x 2.5" SATA/SAS-4 ^[1] Internal M.2: 1 x M.2 (2280/22110), PCIe Gen4 x2 ^[1] Storage card required to support optional drives. Only one card supported, and total drive bandwidth limited to 16i.		



Learn more at: <https://www.gigabyte.com/Enterprise>
* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.
Last updated: Aug 14, 2026

Designed by

