GIGABYTE™

G894-SD1-AAX5

HPC/AI Server - Intel® Xeon® 6700/6500-Series Processors - 8U DP NVIDIA HGX™ B200



Key Features

- NVIDIA HGX™ B200
- 1.8 TB/s GPU-to-GPU bandwidth with NVIDIA NVLink™
- Dual Intel® Xeon® 6700/6500-Series Processors
- 8-Channel DDR5 RDIMM/MRDIMM per CPU with 32 x DIMMs
- Compatible with NVIDIA BlueField®-3 DPUs and NVIDIA ConnectX®-7 NICs
- 2 x 10 Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen5 x4 and x2
- 8 x 2.5" Gen5 NVMe hot-swap bays
- 4 x FHHL dual-slot PCIe x16 slots with Gen5 x16 lanes
- 8 x FHHL single-slot PCIe x16 slots with Gen5 x16 lanes
- Compatible with SupremeRAID™ AE by Graid Technology
- 6+6 3000 W 80 PLUS Titanium redundant power supplies

Specification

Dimensions	8U (W447 x H351 x D923 mm)
Motherboard	MSB4-PE0
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors - Intel® Xeon® 6500-Series Processors Dual processors, TDP up to 350 W
OS Compatibility	OS Support List
Socket	2 x LGA 4710 (Socket E2)
Chipset	System on Chip
Memory	8-Channel DDR5 RDIMM/MRDIMM, 32 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 6000 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s [1] [1] MRDIMMs are supported only on select Intel® Xeon® 6 processors with P-cores and only in a 1DPC configuration.
LAN	**Front:** 2 x 10 Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN **Rear:** 1 x 10/100/1000 Mb/s Management LAN
Video	Integrated in ASPEED® AST2600 - 1 x VGA port
Storage	**Front hot-swap:** 8 x 2.5" Gen5 NVMe **Internal M.2:** 1 x M.2 (2280/22110), PCIe Gen5 x4 1 x M.2 (2280/22110), PCIe Gen5 x2 *Compatible with SupremeRAID™ AE by Graid Technology.
Modular GPU	NVIDIA HGX™ B200 with 8 x SXM GPUs
PCIe Expansion Slots	4 x FHHL x16 (Gen5 x16), dual-slot 8 x FHHL x16 (Gen5 x16), single-slot
I/O Ports	**Front:** 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) **Rear:** 1 x MLAN
TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012
Power Supply	6+6 3000 W 80 PLUS Titanium redundant power supplies AC Input: 115-240 V *The system power supply requires C19 power cord.
System Fans	Motherboard: 2 x 60x60x56mm 4 x 60x60x76mm PCIe slots: 4 x 80x80x56mm GPU tray: 15 x 80x80x80mm
Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Packaging Content	1 x G894-SD1-AAX5 2 x CPU heatsinks 4 x Carriers 1 x L-shape Rail kit
Ordering Part Numbers	6NG894SD1DR000AAX5*

Learn more at: https://www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Jul 20, 2026

Designed by GIGA COMPUTING