GIGABYTE™

H262-Z6A (Rev. 100)

High Density Server - AMD EPYC™ 7002/7001 Series Processors -
2U 4-Node DP 24-Bay Gen4 NVMe/SATA/SAS

Key Features

- Hardware-level root of trust support
- 2U 4-node rear access server system
- Dual AMD EPYC™ 7002/7001 Series processors per node
- 8-Channel DDR4 RDIMM/LRDIMM per CPU with 16 x DIMMs per node
- 8 x 1 Gb/s LAN ports via Intel® I350-AM2
- 1 x CMC port
- 24 x 2.5" Gen4 NVMe/SATA/SAS hot-swap bays
- 4 x M.2 slots with PCIe Gen4 x4
- 8 x LP PCIe Gen4 x16 slots
- 4 x OCP NIC 3.0 PCIe Gen4 x16 slots
- Dual 2200 W 80 PLUS Platinum redundant power supplies

Applications

High Converged Server, Servers for Hybrid/Private Cloud...

Specification

Dimensions	2U 4-Node - Rear access (W440 x H87.5 x D840 mm)
Motherboard	MZ62-HD4
CPU	AMD EPYC™ 7002 Series Processors AMD EPYC™ 7001 Series Processors Dual processor per node, TDP up to 200 W *Contact our sales representatives or technical support for more details about supporting cTDP 240 W CPUs.
Socket	8 x LGA 4094 (Socket SP3)
Chipset	System on Chip
Memory	8-Channel DDR4 RDIMM/LRDIMM, 64 x DIMMs Up to 3200 MT/s
LAN	8 x 1 Gb/s LAN (4 x Intel® I350-AM2), Support NCSI 4 x 10/100/1000 Mb/s Management LAN 1 x CMC port
Video	Integrated in ASPEED® AST2500 x 4 - 4 x Mini-DP
Storage	**Front hot-swap:** 24 x 2.5" Gen4 NVMe/SATA**/SAS** [1] **Internal M.2:** 4 x M.2 (2280/22110), PCIe Gen4 x4 [1] SAS card is required to support SAS drives.
RAID	Require RAID add-in cards
PCIe Expansion Slots	8 x LP x16 (Gen4 x16) 4 x OCP NIC 3.0 (Gen4 x16), Support NCSI
I/O Ports	**Front:** 1 x CMC status LED, 1 x CMC reset button **Rear:** 8 x USB 3.0, 4 x Mini-DP, 8 x RJ45, 4 x MLAN, 1 x CMC port
Backplane Board	PCIe Gen4 x4 or SATA 6 Gb/s or SAS 12 Gb/s
TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM010
Power Supply	Dual 2200 W 80 PLUS Platinum redundant power supplies AC Input: 100-240 V *The system power supply requires C19 power cord.
System Management	ASPEED® AST2500 Baseboard Management Controller ASPEED® AST2520 Chassis Management Controller GIGABYTE Management Console web interface
System Fans	8 x 80x80x38mm
Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Packaging Content	1 x H262-Z6A 8 x CPU heatsinks 1 x 3-Section Rail kit
Ordering Part Numbers	6NH262Z6AMR-00-1*
Optional Parts	- C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - M.2 expansion card - CMTP061: 9CMTP061NR-00* - Ring topology kit: 6NH262Z65SR-00-100 - Mini-DP to D-Sub cable: 25CRN-200801-K1R

Learn more at: https://www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Aug 11, 2026

Designed by GIGA COMPUTING