GIGABYTE™

TO46-SD3-LA07

ORV3 GPU Server - Intel® Xeon® 6700/6500-Series Processors - 4OU DP NVIDIA HGX™ B300 DLC

Key Features

- Liquid-cooled NVIDIA HGX™ B300
- Integrated-manifold DLC solution with leak detection
- 8 x 800 Gb/s OSFP XDR InfiniBand or dual 400 Gb/s Ethernet GPU networking ports
- 1.8 TB/s GPU-to-GPU bandwidth with NVIDIA NVLink™
- Dual Intel® Xeon® 6700/6500-Series Processors
- 8-Channel liquid-cooled DDR5 RDIMM/MRDIMM per CPU with 32 x DIMMs
- Compatible with NVIDIA BlueField®-3 DPUs
- 2 x 10 Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen5 x4 and x2
- 8 x 2.5" Gen5 NVMe hot-swap bays
- 4 x FHHL PCIe x16 slots with Gen5 x16 lanes
- 48 V to 54 V DC Bus Bar power solution

Specification

Dimensions	4OU (W537 x H189.2 x D840 mm)
Motherboard	MSB4-PE3
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors - Intel® Xeon® 6500-Series Processors [DLC] Dual processors, TDP up to 350 W
Socket	2 x LGA 4710 (Socket E2)
OS Compatibility	OS Support List
Chipset	System on Chip
Memory	[DLC] 8-Channel DDR5 RDIMM/MRDIMM, 32 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 6000 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s [1] [1] MRDIMMs are supported only on select Intel® Xeon® 6 processors with P-cores and only in a 1DPC configuration.
LAN	2 x 10 Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN 8 x 800 Gb/s OSFP XDR InfiniBand or dual 400 Gb/s Ethernet, for GPU networking, via NVIDIA ConnectX®-8 SuperNIC™
Video	Integrated in ASPEED® AST2600 - 1 x VGA port
Storage	**Front hot-swap:** 8 x 2.5" Gen5 NVMe **Internal M.2:** 1 x M.2 (2280/22110), PCIe Gen5 x4 1 x M.2 (2280/22110), PCIe Gen5 x2
Modular GPU	[DLC] NVIDIA HGX™ B300 with 8 x SXM GPUs
PCIe Expansion Slots	4 x FHHL x16 (Gen5 x16) *The ambient temperature is limited to 30°C when NVIDIA BlueField®-3 DPUs/SuperNIC™ are installed.
I/O Ports	**Front:** 8 x OSFP, 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN
TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012
System Fans	2 x 80x80x38mm 4 x 92x92x76mm
Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Packaging Content	1 x TO46-SD3-LA07 4 x Carriers 1 x L-shape rail kit
Ordering Part Numbers	6NTO46SD3DR000LA07*

Learn more at: https://www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.
© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Aug 10, 2026

Designed by GIGA COMPUTING