

XV24-SU0-AAJ1

NVIDIA MGX™ Server - Intel® Xeon® 6 Processors R1S -
2U UP 4 x PCIe Gen5 GPUs



Key Features

- Supports up to 4 x dual-slot Gen5 GPUs
 - 4 x NVIDIA H200 NVL PCIe GPUs with 2-way NVLink bridges
 - 4 x NVIDIA RTX PRO™ 6000 Blackwell Server Edition GPUs
- NVIDIA MGX™ modular server design
- Single Intel® Xeon® 6700/6500-Series Processors with 136 PCIe lanes
- 8-Channel DDR5 RDIMM/MRDIMM per CPU with 16 x DIMMs
- 2 x 10 Gb/s LAN ports via Intel® X550-AT2
- 2 x 2.5" Gen5 NVMe hot-swap bays
- 2 x M.2 slots with PCIe Gen5 x4
- 4 x FHFL PCIe x16 (Gen5 x16) for GPUs
- 2 x FHFL PCIe x16 (Gen5 x16) for NVIDIA ConnectX®-7 NICs
- 1 x FHFL PCIe x16 (Gen5 x16) for NVIDIA BlueField®-3 DPUs
- 3+1 2000 W 80 PLUS Titanium redundant power supplies

Specification

Dimensions	2U (W438 x H87 x D900 mm)	PCIe Expansion Slots	4 x FHFL x16 (Gen5 x16), for GPUs 2 x FHFL x16 (Gen5 x16), for NICs 1 x FHFL x16 (Gen5 x16), for DPUs
Motherboard	MSU4-MG0		
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors with 136 PCIe lanes - Intel® Xeon® 6500-Series Processors with 136 PCIe lanes Single processor, TDP up to 350 W		*The system supports 4 x NVIDIA H200 NVL PCIe GPUs at 25°C ambient, arranged as two 2-GPU sets, each with a 2-way NVLink bridge. *The system supports 4 x NVIDIA RTX PRO™ 6000 Blackwell Server Edition GPUs at 25°C ambient.
OS Compatibility	OS Support List	I/O Ports	Front: 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
Socket	1 x LGA 4710 (Socket E2)	TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012 1 x PRoT connector (only enabled on RoT SKU)
Chipset	System on Chip	Power Supply	3+1 2000 W 80 PLUS Titanium redundant power supplies AC Input: 100-240 V
Memory	8-Channel DDR5 RDIMM/MRDIMM, 16 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 6000 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s ^[1] ^[1] MRDIMMs are supported only on select Intel® Xeon® 6 processors with P-cores and only in a 1DPC configuration.	System Fans	2 x 60x60x56mm 4 x 80x80x80mm
LAN	2 x 10 Gb/s LAN (1 x Intel® X550-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x XV24-SU0-AAJ1 2 x CPU heatsinks 1 x Mini-DP to D-Sub cable 2 x GPU power cables (16-pin, 450mm) 2 x GPU power cables (16-pin, 550mm) 1 x DPU power cable (2x PCIe 8pin, 520mm) 2 x Carriers 1 x 3-Section Rail kit
Storage	Front hot-swap: 2 x 2.5" Gen5 NVMe Internal M.2: 2 x M.2 (2242/2260/2280/22110), PCIe Gen5 x4	Ordering Part Numbers	6NXV24SU0DR000AAJ1*
		Optional Parts	- Chassis intrusion switch: 25HA1-R28390-U1R - Cable Management Arm: 25HB2-2AA700-K0R



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Jun 25, 2026

Designed by

