


MH53-G40

Workstation Motherboard

AMD
THREADRIPPER
PRO



Features

- Single AMD Ryzen™ Threadripper™ PRO 7000 WX-Series Processors
- 8-Channel DDR5 RDIMM, 8 x DIMMs
- AMD WRX90 Chipset
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 1 x MCIO 8i connector for 2 x Gen5 NVMe or 8 x SATA 6Gb/s
- 4 x SATA 6Gb/s ports
- 4 x M.2 slots with PCIe Gen5 x4 interface
- 1 x M.2 slot with PCIe Gen3 x1 interface for Wi-Fi add-in cards
- 6 x PCIe Gen5 x16 expansion slots

Specification

Form Factor	E-ATX (304.8W x 330.2D mm)	Internal I/O	1 x CPU fan header, 6 x System fan headers, 1 x Front audio header, 1 x USB 3.2 Gen2 header, 1 x USB 3.2 Gen1 header, 1 x MCIO 8i connector, 4 x SATA ports, 1 x Front panel header, 1 x Backplane board header, 1 x COM header, 1 x PMBus header, 1 x IPMB header, 1 x TPM header
CPU	AMD Ryzen™ Threadripper™ PRO 7000 WX-Series Processors Up to 96 cores, 192 threads Single processor, TDP up to 350W	Rear I/O	1 x USB 3.2 Gen2x2 Type-C, 3 x USB 3.2 Gen2x1 Type-A, 1 x VGA, 1 x COM, 2 x RJ45, 1 x MLAN, 3 x Audio jacks, 1 x ID button
Socket	1 x sTR5	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
Chipset	AMD WRX90	PSU Connectors	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x 6-pin ATX 12V power connector
Memory	8-Channel DDR5 memory, 8 x DIMM slots RDIMM/3DS RDIMM supported Memory speed: Up to 5200 MT/s	Board Management	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
LAN	2 x 10Gb/s LAN ports (1 x Broadcom® BCM57416) Supported NCSI function 1 x 10/100/1000 Mbps Management LAN	OS Compatibility	Red Hat Enterprise Linux (x86_64) Ubuntu (x86_64) Windows 11 (x64)
Video	Integrated in ASPEED® AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp	Operating Properties	Operating temperature: 10°C to 40°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Audio	Realtek® ALC897 HD Audio Codec Supports 2/4/5.1/7.1 channel configurations 3 x Audio jacks (Audio in/Audio out/Mic)	Retail Packaging Content	1 x MH53-G40, 1 x I/O shield, 1 x Quick start guide Single Box dimensions: 409 x 355 x 78 mm Quantity: 10 x single boxes in one carton
Storage	1 x MCIO 8i connector for 2 x Gen5 NVMe or 8 x SATA 6Gb/s 4 x SATA 6Gb/s ports 4 x M.2 slots (M-key, PCIe Gen5 x4, support 2280/22110 cards)	Bulk Packaging Content	10 x MH53-G40, 10 x I/O shields Carton dimensions: 600 x 473 x 517 mm
RAID	RAID 0/1/10/5	Reference Numbers	Retail: 9MH53G40MR-000-1* Bulk: 9MH53G40NR-000-1*
Expansion Slots	6 x PCIe Gen5 x16 slots 4 x M.2 slots for storage (M-key, PCIe Gen5 x4, support 2280/22110) 1 x M.2 slot for Wi-Fi (E-key, PCIe Gen3 x1, support 2230 cards) 1 x MCIO 8i (Gen5 x8 or SATA) connector		



Learn more about GIGABYTE server at <https://www.gigacomputing.com>

Designed by



* All specifications are subject to change without notice. Please visit our website for the latest information.
* AMD, the AMD Arrow logo, Ryzen, Threadripper and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.