


MZ33-CP1

Server Motherboard - E-ATX UP



Features

- Single AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 12 x DIMMs
- 2 x 1Gb/s LAN ports via Intel® I210-AT
- 4 x MCIO 8i connectors with PCIe Gen5 x8 interface
- 2 x MCIO 8i connectors with PCIe Gen4 x8 or SATA interface
- 1 x M.2 slot with PCIe Gen3 x4 interface
- 4 x PCIe Gen5/Gen4 x16 expansion slots
- 1 x OCP NIC 3.0 PCIe Gen5 x16 slot

Specification

Form Factor	E-ATX (W304.8W x D330.2 mm)	Internal I/O	1 x CPU fan header, 5 x System fan headers, 6 x MCIO 8i connectors, 1 x Front panel header, 1 x Backplane board header, 1 x PMBus header, 1 x IPMB header, 1 x USB 3.2 Gen1 x2 header, 1 x USB 2.0 x2 header, 1 x TPM header
CPU	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Single processor, cTDP up to 500W	OS Compatibility	Microsoft Windows Server Red Hat Enterprise Linux server SUSE Linux Enterprise server Ubuntu VMware ESXi Citrix Hypervisor
Socket	1 x LGA 6096, Socket SP5	Board Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	PSU Connectors	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x 6-pin ATX 12V power connector 1 x 4-pin 12V standby power connector
Memory	12 x DIMM slots 12-Channel DDR5 memory architecture [EPYC 9005] RDIMM: Up to 6000 MT/s [EPYC 9004] RDIMM: Up to 4800 MT/s	Operating Properties	Operating temperature: 10°C to 40°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
LAN	2 x 1Gb/s LAN (2 x Intel® I210-AT) - Support NCSI function 1 x 10/100/1000 Mbps Management LAN	Retail Packaging Content	1 x MZ33-CP1, 1 x I/O shield, 1 x Quick start guide, 1 x MCIO 8i to 8 x SATA 6Gb/s cable (600mm) Single Box dimensions: 409 x 355 x 78 mm
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Bulk Packaging Content	10 x MZ33-CP1, 10 x I/O shields Carton dimensions: 600 x 473 x 517 mm
Audio	N/A	Reference Numbers	Retail: 9MZ33CP1MR-000-3* Bulk: 9MZ33CP1NR-000-3*
Storage Interface	4 x MCIO 8i for 8 x Gen5 NVMe 2 x MCIO 8i for 4 x Gen4 NVMe or 16 x SATA 6Gb/s 1 x M.2 (2280/22110), PCIe Gen3 x4	Optional parts	MCIO 8i to 2 x MCIO 4i cable (550mm): 25CF9-550700-A4R
RAID	N/A		
Expansion Slots	3 x PCIe Gen Gen5 x16 slots 1 x PCIe Gen Gen4 x16 slot 1 x OCP NIC 3.0 PCIe Gen5 x16 slot - Supports NCSI function		
Security Modules	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM012		
Rear I/O	2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

