


MZ73-LM2

Server Motherboard - E-ATX DP



Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 2 x MCIO 8i connectors with PCIe Gen5 x8 or SATA interface
- 1 x SlimSAS 4i connector with SATA interface
- 1 x M.2 slot with PCIe Gen5 x4 interface
- 4 x PCIe Gen5 x16 expansion slots
- ASPEED® AST2600 Baseboard Management Controller

Specification

Form Factor	E-ATX (W305 x D330 mm)	Internal I/O	2 x CPU fan headers (4pin), 2 x CPU fan headers (3pin), 4 x System fan headers, 1 x USB 3.2 Gen1 x2 header, 2 x MCIO 8i connectors, 1 x SlimSAS 4i connector, 1 x Front panel header, 1 x Backplane board header, x PMBus connector, 1 x IPMB connector
CPU	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Dual processors, cTDP up to 500W	OS Compatibility	Windows Server, Red Hat Enterprise Linux server, Ubuntu, SUSE Linux Enterprise server, VMware ESXi, Citrix Hypervisor
Socket	2 x LGA 6096, Socket SP5	Board Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	PSU Connectors	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 3 x 6-pin ATX 12V power connectors
Memory	24 x DIMM slots 12-Channel DDR5 RDIMM [EPYC 9005] Up to 6400 MT/s [EPYC 9004] Up to 4800 MT/s	Operating Properties	Operating temperature: 10°C to 40°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
LAN	2 x 10Gb/s LAN (1 x Broadcom® BCM57416) - Support NCSI 1 x 10/100/1000 Mbps Management LAN	Retail Packaging Content	1 x MZ73-LM2, 1 x I/O shield, 1 x Quick start guide, 1 x SlimSAS 4i to 4 x SATA 6Gb/s cable (600mm) Single Box dimensions: 409 x 355 x 78 mm Carton dimensions: 729 x 415 x 432 mm Quantity: 10 x single boxes in one carton
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Bulk Packaging Content	10 x MZ73-LM2, 10 x I/O shields Carton dimensions: 600 x 473 x 517 mm
Audio	N/A	Reference Numbers	Retail: 9MZ73LM2MR-000-3* Bulk: 9MZ73LM2NR-000-3* Optional parts: - 500W CPU fansink: 25ST0-0Z1921-C1R
Storage Interface	2 x MCIO 8i for 4 x Gen5 NVMe or 16 x SATA 1 x SlimSAS 4i for 4 x SATA 1 x M.2 (2280/22110), PCIe Gen5 x4		
RAID	N/A		
Expansion Slots	4 x PCIe Gen Gen5 x16 slots		
Security Modules	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM012		
Rear I/O	2 x USB 3.2 Gen1, 1 x VGA, 1 x COM, 2 x RJ45, 1 x MLAN		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.
* All other brands, logos and names are property of their respective owners.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

