

# R162-ZA0

Rack Server - 1U UP 4-Bay



## Features

- Hardware-level root of trust support
- Single AMD EPYC™ 7003 Series processors
- 8-Channel RDIMM/LRDIMM DDR4, 16 x DIMMs
- 2 x 1GbE LAN ports
- 1 x Dedicated management port
- 4 x 3.5/ 2.5" SATA hot-swappable HDD/SSD bays
- Ultra-Fast M.2 with PCIe Gen4 x4 interface
- 2 x PCIe Gen4 x16 expansion slots
- 1 x internal PCIe Gen4 x16 expansion slot
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 1 x OCP 2.0 Gen3 x8 mezzanine slot
- 1+1 800W (240V) 80 PLUS Platinum redundant power supply

## Specification

<b>Dimensions</b>	1U (W438 x H43.5 x D730 mm)	<b>Front I/O</b>	2 x USB 3.0
<b>Motherboard</b>	MZA2-CE0 Rev. 3.0	<b>Rear I/O</b>	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN
<b>CPU</b>	AMD EPYC™ 7003 Series processors Single processor, 7nm technology, cTDP up to 240W Up to 64-core, 128 threads per processor Compatible with AMD EPYC™ 7002 Series processors	<b>Backplane I/O</b>	Speed and bandwidth:SATA 6Gb/s
<b>Chipset</b>	System on Chip	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>Memory</b>	8-Channel DDR4 memory, 16 x DIMM slots RDIMM/LRDIMM modules up to 128GB supported Memory speed: Up to 3200 / 2933 MHz	<b>Power Supply</b>	1+1 800W 80 PLUS Platinum redundant power supply AC Input: 100-240V
<b>LAN</b>	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	<b>System Management</b>	Aspeed® AST2500 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Video</b>	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp	<b>OS Compatibility</b>	Windows Server 2016 / 2019 / 2022 RHEL 8.3 / 9 (x64) or later SLES 12 SP5 / 15 SP2 (x64) or later Ubuntu 18.04.5 LTS / 20.04 LTS / 22.04 (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update1 or later Citrix Hypervisor 8.2.0 or later
<b>Storage</b>	4 x 3.5/ 2.5" SATA hot-swappable HDD/SSD bays SATA devices supported only	<b>System Fans</b>	6 x 40x40x28mm (25,000rpm)
<b>RAID</b>	N/A	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Peripheral Drives</b>	1 x Slim type ODD as an option NOTE: For 12.7mm ODD only	<b>Reference Numbers</b>	Barebone package: 6NR162ZA0MR-00 Rev. A00 - Motherboard: 9MZA2CE0NR-00 Rev. 3.0 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-443201-A0R - Back plane board: 9CBP1042NR-00 - Power supply: 25EPO-208004-L0S - Riser card - CRS101E: 9CRS101ENR-00 - Internal Riser card - CRS101H: 9CRS101HNR-00
<b>Expansion Slots</b>	Riser Card CRS101E: 1 x PCIe x16 slot (Gen4 x16), FHHL Riser Card CRS101E: 1 x PCIe x16 slot (Gen4 x8 or x16), FHHL Internal Riser Card CRS101H: 1 x PCIe x16 slot (Gen4 x16), FHHL 1 x OCP 3.0 mezzanine slot with PCIe Gen4 x16 bandwidth 1 x OCP 2.0 mezzanine slot with PCIe Gen3 x0 or x8 bandwidth 1 x M.2 slot: M-key, PCIe Gen4 x4 per slot - Supports NGFF-2280/22110 cards		



Learn more about GIGABYTE server solutions, visit [www.gigabyte.com/Enterprise](http://www.gigabyte.com/Enterprise)

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* AMD, and the AMD Arrow logo, AMD EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.

\* All other brands, logos and names are property of their respective owners.

© 2022 GIGABYTE Technology Co., Ltd. All rights reserved.