

R164-S30-AAG1

Rack Server - 1U UP 4-Bay NVMe/SATA



Key Features

- Single Intel® Xeon® 6 Processors, LGA 4710
- 8-Channel DDR5 RDIMM / MCR DIMM, 16 x DIMMs
- Dual ROM Architecture
- 1 x 1Gb/s LAN port via Intel® I210-AT
- 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 hot-swappable bays
- 1 x M.2 slot with PCIe Gen5 x2 interface
- 1 x M.2 slot with PCIe Gen5 x2 interface, shared with SATA support
- 2 x FHHL PCIe Gen5 x16 slots
- 2 x OCP 3.0 Gen5 x16 slots
- Dual 800W 80 PLUS Titanium redundant power supply

Application

Networking, Hybrid/Private Cloud Server...

Specification

Dimensions 1U (W438 x H43.5 x D710 mm)

Motherboard MS34-DC0

CPU Intel® Xeon® 6 Processors
 - Intel® Xeon® 6700E-Series Processors
 - Intel® Xeon® 6700P-Series Processors
 - Intel® Xeon® 6500P-Series Processors
 Single processor, TDP up to 350W

Sock 1 x LGA 4710 (Socket E2)

Chipset System on Chip

Memory 8-Channel DDR5 RDIMM / MCR DIMM, 16 x DIMM slots
 RDIMM: Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC)
 MCR DIMM: Up to 8000 MT/s (*MCR DIMMs are only supported with Intel Xeon 6 Processors with P-cores and in a 1DPC configuration.)

LAN 1 x 1Gb/s LAN port (1 x Intel® I210-AT) - supports NCSI function
 1 x 10/100/1000 Mbps Management LAN

Video Integrated in ASPEED® AST2600
 2D Video Graphic Adapter with PCIe bus interface
 1920x1200@60Hz 32bpp

Storage 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4* hot-swappable bays
 *SAS card is required to support SAS drives.

RAID Require RAID add-in cards

Expansion Slots 2 x FHHL PCIe Gen5 x16 slots
 2 x OCP 3.0 Gen5 x16 slots (supports NCSI function)
 2 x M.2 slots (M-key, PCIe Gen5 x2, support 2280/22110 cards)
 - 1 x M.2 slot is shared with SATA support

I/O Ports Front: 2 x USB 3.2 Gen1
 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 1 x RJ45, 1 x MLAN
 Internal: 1 x TPM header, 1 x PRoT connector, 1 x VROC connector

Backplane Board PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s

Security Modules 1 x TPM header with SPI interface
 - Optional TPM2.0 kit: CTM012
 1 x PRoT module connector (M.2 M-key)
 - Optional PRoT module (AST1060 solution): CSC1200

Power Supply Dual 800W 80 PLUS Titanium redundant power supply
 AC Input: 100-240V

System Management ASPEED® AST2600 management controller
 GIGABYTE Management Console (AMI MegaRAC SP-X)

System Fans 2 x 40x40x28mm (25,000rpm), 4 x 40x40x56mm (32,000rpm)

Operating Properties Operating temperature: 10°C to 35°C
 Operating humidity: 8%-80% (non-condensing)
 Non-operating temperature: -40°C to 60°C
 Non-operating humidity: 20%-95% (non-condensing)

Packaging Content 1 x R164-S30-AAG1
 1 x CPU heatsink
 1 x Mini-DP to D-Sub cable
 2 x Carriers
 1 x 2-Section Rail kit

Part Numbers Barebone package: 6NR164S30DR000AAG1*
 - 2-Section Rail kit (CMA not supported): 25HB2-3A0203-K0R
 - CPU heatsink: 25ST1-4Z3200-S7R
 - Mini-DP to D-Sub cable: 25CRN-200801-K1R
 - Power supply: 25EP0-20800A-G1S



Learn more about GIGABYTE server at <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
 * Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
 * All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

