


# E283-Z90-AAV1

Edge Server - 2U DP 4-Bay Gen4 NVMe/SATA/SAS Titanium



### Key Features

- Dual AMD EPYC™ 9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- 2 x 1Gb/s LAN ports via Intel® I350-AM2
- 4 x 2.5" Gen4 NVMe/SATA/SAS hot-swap bays on the rear side
- 2 x M.2 slots with PCIe Gen3 x4 and x2 interface
- 6 x FHHL PCIe Gen5 x16 and x8 slots
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 1600W 80 PLUS Titanium redundant power supply

### Applications

Networks Server, Servers for Hybrid/Private Cloud, Edge Server...

### Specification

|                  |                                                                                                                                                                                                                                       |                       |                                                                                                                              |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------|
| Dimensions       | 2U (W438 x H87.5 x D625 mm)                                                                                                                                                                                                           | PCIe Expansion Slots  | 6 x FHHL PCIe Gen5 x16 and x8<br>2 x OCP NIC 3.0 PCIe Gen5 x16, Support NCSI                                                 |
| Motherboard      | MZ93-FS0                                                                                                                                                                                                                              | I/O Ports             | <b>Front:</b><br>2 x USB 3.2 Gen1<br><b>Rear:</b><br>2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN                       |
| CPU              | AMD EPYC™ 9005 Series Processors<br>AMD EPYC™ 9004 Series Processors<br>Dual processor, cTDP up to 400W                                                                                                                               | Backplane Board       | PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s                                                                                     |
| OS Compatibility | <a href="#">OS Support List</a>                                                                                                                                                                                                       | TPM                   | 1 x TPM header (SPI), Optional TPM2.0 kit: CTM010                                                                            |
| Socket           | 2 x LGA 6096 (Socket SP5)                                                                                                                                                                                                             | Power Supply          | Dual 1600W 80 PLUS Titanium redundant power supply<br>AC Input: 100-240V                                                     |
| Chipset          | System on Chip                                                                                                                                                                                                                        | System Management     | ASPEED® AST2600 Baseboard Management Controller<br>GIGABYTE Management Console web interface                                 |
| Memory           | 12-Channel DDR5 RDIMM, 24 x DIMMs<br>Up to 4800 MT/s                                                                                                                                                                                  | System Fans           | 4 x 80x80x38mm                                                                                                               |
| LAN              | 2 x 1Gb/s LAN (1 x Intel® I350-AM2), Support NCSI<br>1 x 10/100/1000 Mbps Management LAN                                                                                                                                              | Operating Properties  | Operating: 10°C to 35°C, 8% to 80% (non-condensing)<br>Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)             |
| Video            | Integrated in ASPEED® AST2600<br>- 1 x Mini-DP                                                                                                                                                                                        | Packaging Content     | 1 x E283-Z90-AAV1<br>2 x CPU heatsinks<br>1 x Mini-DP to D-Sub cable                                                         |
| Storage          | <b>Rear hot-swap:</b><br>4 x 2.5" Gen4 NVMe/SATA/SAS <sup>[1]</sup><br><b>Internal M.2:</b><br>1 x M.2 (2280/22110), PCIe Gen3 x4<br>1 x M.2 (2280/22110), PCIe Gen3 x2<br><sup>[1]</sup> SAS card is required to support SAS drives. | Ordering Part Numbers | 6NE283Z90DR000ABV1*                                                                                                          |
| RAID             | Require RAID add-in cards                                                                                                                                                                                                             | Optional Parts        | - 2-Section Rail kit (385-480mm): 25HB2-3A0204-K0R ( <b>MOQ: 500</b> )<br>- 2-Section Rail kit (660-840mm): 25HB2-3A0203-K0R |



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

