## G294-Z43-AAP2

HPC/AI Server - 2U DP 16 x PCIe Gen5 GPUs







## **Key Features**

- Supports up to 16 x Single slot Gen5 GPUs
- Dual AMD EPYC<sup>™</sup> 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 4 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 4 x 2.5" SATA/SAS-4 hot-swap bays
- 16 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x LP PCIe Gen5 x16 slots for add-in cards
- Dual 3000W 80 PLUS Titanium redundant power supply

## **Applications**

Al Platform, Al Inference Server, Visual Computing...

Sn	Acit	icati	n
၁ပ	CUII	Itali	ווטו

Dimensions	2U (W448 x H87.5 x D850 mm)	PCIe Expansion Slots	16 x FHFL PCIe Gen5 x16, for GPUs 2 x LP PCIe Gen5 x16, for add-in cards	
Motherboard	MZ43-G20		·	
CPU	AMD EPYC <sup>™</sup> 9005 Series Processors AMD EPYC <sup>™</sup> 9004 Series Processors Dual processor, cTDP up to 240W - At ambient 30°C, cTDP up to 300W	I/O Ports	<b>Rear:</b> 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN	
		Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s	
		TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010	
OS Compatibility	OS Support List	Power Supply	Dual 3000W 80 PLUS Titanium redundant power supply *The system power supply requires C19 power cord.	
Socket	2 x LGA 6096 (Socket SP5)			
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface	
Memory	12-Channel DDR5 RDIMM, 24 x DIMMs [EPYC 9005] Up to 6400 MT/s [EPYC 9004] Up to 4800 MT/s	Ū	· ·	
		System Fans	8 x 80x80x80mm	
LAN	2 x 10Gb/s LAN (1 x Broadcom® BCM57416), Support NCSI 1 x 10/100/1000 Mbps Management LAN	Operating	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)	
		Properties		
) C 1	·	Packaging Content	1 x G294-Z43-AAP2	
Video	Integrated in ASPEED® AST2600 - 1 x VGA port		2 x CPU heatsinks 1 x L-shape Rail kit	
Otana na	Formath at a comm	Ondering Deet	CNO.00.47.40DD000.4.0D0+	
Storage	Front hot-swap: 4 x 2.5" Gen5 NVMe/SATA/SAS-4 [1]	Ordering Part Numbers	6NG294Z43DR000ACP2*	
	4 x 2.5" SATA/SAS-4 <sup>[1]</sup>			
	[1] SAS card is required to support SAS drives.			
RAID	Require RAID add-in cards			



