

# G363-SR0-AAX4

HPC/AI Server - 3U DP HGX™ H200 4-GPU



## Key Features

- NVIDIA HGX™ H200 4-GPU
- 900GB/s 4th-generation NVIDIA NVLink™
- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 16 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 2 x 1Gb/s LAN ports via Intel® I350-AM2
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen4 x4 interface
- 6 x LP PCIe Gen5 x16 slots
- 2+1 3000W 80 PLUS Titanium redundant power supplies

## Applications

AI Platform, AI Training Server, AI Inference Server, High-Performance Computing Server...

## Specification

Dimensions	3U (W448 x H131 x D850.2 mm)	Modular GPU	NVIDIA HGX™ H200 with 4 x SXM GPUs
Motherboard	MS63-HD2	PCIe Expansion Slots	6 x LP PCIe Gen5 x16
CPU	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350W	I/O Ports	<b>Front:</b> 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN (default) <b>Rear:</b> 2 x RJ45, 1 x MLAN
OS Compatibility	<a href="#">OS Support List</a>	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Socket	2 x LGA 4677 (Socket E)	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Chipset	Intel® C741	Power Supply	2+1 3000W 80 PLUS Titanium redundant power supplies AC Input: 115-240V  *The system power supply requires C19 power cord.
Memory	8-Channel DDR5 RDIMM, 16 x DIMMs [5th Gen Intel Xeon] Up to 5600 MT/s [4th Gen Intel Xeon] Up to 4800 MT/s [Intel Xeon Max Series] Up to 4800 MT/s	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
LAN	<b>Front:</b> 2 x 1Gb/s LAN (1 x Intel® I350-AM2), Support NCSI 1 x 10/100/1000 Mbps Management LAN <b>Rear:</b> 2 x 10Gb/s LAN (1 x Broadcom® BCM57416), Support NCSI 1 x 10/100/1000 Mbps Management LAN	System Fans	7 x 80x80x80mm
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Storage	<b>Front hot-swap:</b> 8 x 2.5" Gen5 NVMe/SATA/SAS-4 <sup>[1]</sup> <b>Internal M.2:</b> 1 x M.2 (2280/22110), PCIe Gen4 x4  <sup>[1]</sup> SAS card is required to support SAS drives.	Packaging Content	1 x G363-SR0-AAX4 2 x CPU heatsinks 1 x Mini-DP to D-Sub cable 6 x Carriers 1 x L-shape Rail kit
RAID	Intel® SATA RAID 0/1/10/5 Support <b>optional</b> RAID add-in cards	Ordering Part Numbers	6NG363SR0DR000ABX4*



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

