


G894-AD3-AAX7

HPC/AI Server - Intel® Xeon® 6 - 8U DP NVIDIA HGX™ B300



Key Features

- NVIDIA HGX™ B300
- 8 x 800 Gb/s OSFP InfiniBand XDR / Dual 400 Gb/s Ethernet GPU networking ports via onboard NVIDIA ConnectX®-8 SuperNIC™
- 1.8TB/s GPU-to-GPU bandwidth with NVIDIA NVLink™ and NVSwitch™
- Dual Intel® Xeon® 6900-Series Processors
- 12-Channel DDR5 RDIMM / MRDIMM, 24 x DIMMs
- Compatible with NVIDIA® BlueField®-3 DPUs
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen5 x4 and x2 interface
- 8 x 2.5" Gen5 NVMe hot-swap bays
- 4 x FHHL PCIe Gen5 x16 slots
- 12 x 3000W 80 PLUS Titanium redundant power supplies

Applications

AI Platform, AI Training Server, AI Inference Server, High-Performance Computing Server...

Specification

Dimensions	8U (W447 x H351 x D923 mm)	Modular GPU	NVIDIA HGX™ B300 with 8 x SXM GPUs
Motherboard	MAB4-PE2	PCIe Expansion Slots	4 x FHHL PCIe Gen5 x16
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6900-Series Processors Dual processor, TDP up to 500W	I/O Ports	Front: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) Rear: 1 x MLAN
Socket	2 x LGA 7529 (Socket BR)	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM012
Chipset	System on Chip	Power Supply	12 x 3000W 80 PLUS Titanium redundant power supplies *The system power supply requires C19 power cord.
Memory	12-Channel DDR5 RDIMM/MRDIMM, 24 x DIMMs [RDIMM] Up to 6400 MT/s [MRDIMM] Up to 8800 MT/s ^[1] ^[1] MRDIMMs are only supported with Intel® Xeon® 6 Processors with P-cores.	System Fans	Motherboard: 2 x 60x60x56mm 4 x 60x60x76mm OSFP ports: 4 x 40x40x56mm PCIe slots: 2 x 80x80x56mm GPU tray: 15 x 80x80x80mm
LAN	Front: 2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN Rear: 8 x 800 Gb/s OSFP InfiniBand XDR / Dual 400 Gb/s Ethernet, for GPU networking 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Packaging Content	1 x G894-AD3-AAX7 2 x CPU heatsinks 2 x Carriers 1 x L-shape Rail kit
Storage	Front hot-swap: 8 x 2.5" Gen5 NVMe Internal M.2: 1 x M.2 (2280/22110), PCIe Gen5 x4 1 x M.2 (2280/22110), PCIe Gen5 x2		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

