

# H253-Z10-AAP1



High Density Server - AMD EPYC™ 9004 - 2U 4-Node UP 8-Bay E1.S Gen4 NVMe

## Key Features

- 2U 4-node front access server system
- Single AMD EPYC™ 9004 Series Processors per node
- 12-Channel DDR5 RDIMM, 24 x DIMMs per node
- Dual ROM Architecture
- 8 x 1Gb/s LAN ports via Intel® I350-AM2
- 2 x CMC ports
- 8 x E1.S Gen4 NVMe hot-swap bays
- 12 x M.2 slots with PCIe Gen5 x4 and SATA interface
- 4 x LP PCIe Gen5 x16 slots
- 4 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 3000W 80 PLUS Titanium redundant power supply

## Applications

High-Performance Computing Server, High Converged Server...

## Specification

Dimensions	2U 4-Node - Front access (W447 x H86.8 x D902 mm)	PCIe Expansion Slots	4 x LP PCIe Gen5 x16 4 x OCP NIC 3.0 PCIe Gen5 x16
Motherboard	MZ13-SH0	I/O Ports	<b>Front:</b> 8 x USB 3.2 Gen1, 4 x Mini-DP, 8 x RJ45, 4 x MLAN <b>Rear:</b> 2 x CMC ports
CPU	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Single processor per node, cTDP up to 300W - At 30°C ambient, cTDP up to 400W	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
OS Compatibility	<a href="#">OS Support List</a>	Power Supply	Dual 3000W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
Socket	4 x LGA 6096 (Socket SP5)	System Management	ASPEED® AST2600 Baseboard Management Controller ASPEED® AST2520 Chassis Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	System Fans	4 x 80x80x80mm (16,500rpm)
Memory	12-Channel DDR5 RDIMM, 96 x DIMMs [EPYC 9005] Up to 4800 MT/s (1DPC), 4000 MT/s (1R 2DPC), 3600 MT/s (2R 2DPC) [EPYC 9004] Up to 4800 MT/s (1DPC), 3600 MT/s (2DPC)	Operating Properties	Operating: 10°C~35°C, 8%~80% (non-condensing) Non-operating: -40°C~60°C, 20%~95% (non-condensing)
LAN	8 x 1Gb/s LAN (4 x Intel® I350-AM2), Support NCSI 4 x 10/100/1000 Mbps Management LAN 2 x CMC ports	Packaging Content	1 x H253-Z10-AAP1 4 x CPU heatsinks 1 x Mini-DP to D-Sub cable 1 x L-shape Rail kit
Video	Integrated in ASPEED® AST2600 x 4 - 4 x Mini-DP	Ordering Part Numbers	6NH253Z10DR000ABP1*
Storage	<b>Front hot-swap:</b> 8 x 9.5mm E1.S Gen4 NVMe <b>Internal M.2:</b> 4 x M.2 (2280/22110), PCIe Gen5 x4 8 x M.2 (2280), SATA	Optional Parts	- E1.S Latch with dummy tray (24 in 1): 6NH253Z10S1000AAP11 - C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

