

# R183-Z95-AAD1

Rack Server - 1U DP 6-Bay E1.S NVMe + 8-Bay Gen5 NVMe/SATA/SAS-4 Platinum



## Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- 2 x 1Gb/s LAN ports via Intel® I350-AM2
- 6 x E1.S NVMe hot-swap bays
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 3 x M.2 slots with PCIe Gen3 x4 and x2 interface
- 2 x FHHL PCIe Gen5 x16 slots
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 1600W 80 PLUS Platinum redundant power supply

## Applications

Networks Server, Servers for Hybrid/Private Cloud...

## Specification

|                  |                                                                                                                                                                                                                                                                 |                       |                                                                                                                  |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------|
| Dimensions       | 1U (W438 x H43.5 x D815 mm)                                                                                                                                                                                                                                     | PCIe Expansion Slots  | 2 x FHHL PCIe Gen5 x16<br>2 x OCP NIC 3.0 PCIe Gen5 x16, Support NCSI                                            |
| Motherboard      | MZ93-FS1                                                                                                                                                                                                                                                        | I/O Ports             | <b>Front:</b><br>1 x USB 3.2 Gen1<br><b>Rear:</b><br>2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN           |
| CPU              | AMD EPYC™ 9005 Series Processors<br>AMD EPYC™ 9004 Series Processors<br>Dual processor, cTDP up to 300W<br>- OCP NIC 3.0 ≤ 21W at 30°C ambient, cTDP up to 400W                                                                                                 | Backplane Board       | PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s                                                                       |
| OS Compatibility | <a href="#">OS Support List</a>                                                                                                                                                                                                                                 | TPM                   | 1 x TPM header (SPI), Optional TPM2.0 kit: CTM010                                                                |
| Socket           | 2 x LGA 6096 (Socket SP5)                                                                                                                                                                                                                                       | Power Supply          | Dual 1600W 80 PLUS Platinum redundant power supply<br>AC Input: 100-240V                                         |
| Chipset          | System on Chip                                                                                                                                                                                                                                                  | System Management     | ASPEED® AST2600 Baseboard Management Controller<br>GIGABYTE Management Console web interface                     |
| Memory           | 12-Channel DDR5 RDIMM, 24 x DIMMs<br>[EPYC 9005] Up to 6400 MT/s<br>[EPYC 9004] Up to 4800 MT/s                                                                                                                                                                 | System Fans           | 8 x 40x40x56mm                                                                                                   |
| LAN              | 2 x 1Gb/s LAN (1 x Intel® I350-AM2), Support NCSI<br>1 x 10/100/1000 Mbps Management LAN                                                                                                                                                                        | Operating Properties  | Operating: 10°C to 35°C, 8% to 80% (non-condensing)<br>Non-operating: -40°C to 60°C, 20% to 95% (non-condensing) |
| Video            | Integrated in ASPEED® AST2600<br>- 1 x Mini-DP                                                                                                                                                                                                                  | Packaging Content     | 1 x R183-Z95-AAD1<br>2 x CPU heatsinks<br>1 x Mini-DP to D-Sub cable<br>1 x 2-Section Rail kit                   |
| Storage          | <b>Front hot-swap:</b><br>6 x 9.5mm E1.S NVMe<br>8 x 2.5" Gen5 NVMe/SATA/SAS-4 <sup>[1]</sup><br><b>Internal M.2:</b><br>2 x M.2 (2280/22110), PCIe Gen3 x4<br>1 x M.2 (2280/22110), PCIe Gen3 x2<br><sup>[1]</sup> SAS card is required to support SAS drives. | Ordering Part Numbers | 6NR183Z95DR000ACD1*                                                                                              |
| RAID             | Require RAID add-in cards                                                                                                                                                                                                                                       | Optional Parts        | - 3-Section Rail kit (Supports CMA): 25HB2-A56121-K0R<br>- Cable Management Arm: 25HB1-R18300-K0R                |



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

