

W773-H5D-AA01

GPU Workstation - AMD Ryzen™ Threadripper™ PRO 9000/7000 WX



Key Features

- Supports up to 4 x Dual slot Gen5 GPUs
- Single AMD Ryzen™ Threadripper™ PRO 9000/7000 WX-Series Processors
- 8-Channel DDR5 ECC RDIMM, 8 x DIMMs
- AMD WRX90 Chipset
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 4 x M.2 slots with PCIe Gen5 x4 interface
- Up to 8 x 3.5"/2.5" SATA bays
- 6 x PCIe Gen5 x16 slots
- Single 2000W ATX 80 PLUS Gold power supply

Applications

AI Platform, AI Training Server, AI Inference Server, Visual Computing, High-Performance Computing Server, Servers for Hybrid/Private Cloud...

Specification

Dimensions	Pedestal (W218 x H455 x D726.3 mm)	Peripheral Drives	5.25" space reserved for ODD device
Motherboard	MH53-G40	I/O Ports	Front: 3 x USB 3.2 Gen1 Rear: 1 x USB 3.2 Gen2x2, 3 x USB 3.2 Gen2x1, 1 x VGA, 2 x RJ45, 1 x MLAN
CPU	AMD Ryzen™ Threadripper™ PRO 9000 WX-Series Processors AMD Ryzen™ Threadripper™ PRO 7000 WX-Series Processors Single processor, TDP up to 350W	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Socket	1 x sTR5	Power Supply	Single 2000W ATX 80 PLUS Gold power supply AC Input: 100-240V *The system power supply requires C19 power cord.
Chipset	AMD WRX90	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	8-Channel DDR5 ECC RDIMM, 8 x DIMMs [Ryzen Threadripper PRO 9000 WX] Up to 6400 MT/s [Ryzen Threadripper PRO 7000 WX] Up to 5200 MT/s	System Fans	Middle: 3 x 120x120x38mm Rear: 1 x 120x120x25mm
LAN	2 x 10Gb/s LAN (1 x Broadcom® BCM57416), Support NCSI 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Packaging Content	1 x W773-H5D-AA01 1 x CPU fansink
Audio	Realtek® ALC897 HD Audio Codec Supports 2/4/5.1/7.1 channel configurations Rear 3 x Audio jacks (Audio in/Audio out/Mic) Front 2 x Audio jacks (Audio out/Mic)	Ordering Part Numbers	6NW773H5DMR000AB01*
Storage	Front hot-swap: 4 x 3.5"/2.5" SATA Optional 4 x 3.5"/2.5" SATA Internal M.2: 4 x M.2 (2280/22110), PCIe Gen5 x4 *Storage card is required to support NVMe and SAS drives.	Optional Parts	- Rail kit for W7x3 series ((A)+(B)+(C)+(D)): (A) 25HB2-A66126-K0R (Slide Rail), Q'ty: 1 set (B) 25HB4-W77304-C0R (Rack Ear Right), Q'ty: 1 set (C) 25HB4-W77305-C0R (Rack Ear Left), Q'ty: 1 set (D) 25HB7-W77300-C0R (Top Cover for Assembly), Q'ty: 1 set
RAID	RAID 0/1/10/5		



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

