

XV24-SX0-AAJ1

NVIDIA MGX™ Server - 2U DP 4 x PCIe Gen5 GPUs



Key Features

- NVIDIA MGX™ modular server design
- Supports up to 4 x Dual slot Gen5 GPUs
- Supports 4 x NVIDIA H200 NVL PCIe GPUs with 2-way NVLink bridges
- Dual Intel® Xeon® 6 Processors, LGA 4710
- 8-Channel DDR5 RDIMM / MRDIMM, 32 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Intel® X550-AT2
- 4 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 2 x M.2 slots with PCIe Gen5 x2 interface
- 4 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x FHFL PCIe Gen5 x16 slots for NVIDIA ConnectX®-7 NICs
- 1 x FHFL PCIe Gen5 x16 slot for NVIDIA BlueField®-3 DPUs
- 3+1 2000W 80 PLUS Titanium redundant power supplies

Specification

Dimensions	2U (W438 x H87 x D900 mm)	PCIe Expansion Slots	4 x FHFL PCIe Gen5 x16, for GPUs 2 x FHFL PCIe Gen5 x16, for NICs 1 x FHFL PCIe Gen5 x16, for DPUs <small>*The system supports 4 x NVIDIA H200 NVL PCIe GPUs at 25°C ambient, arranged as two 2-GPU sets, each with a 2-way NVLink bridge. *The system is only validated with a uniform GPU model.</small>
Motherboard	MSX4-MG0	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors - Intel® Xeon® 6500-Series Processors Dual processor, TDP up to 350W	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
OS Compatibility	OS Support List	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM012 1 x PRoT connector (only enabled on RoT SKU)
Socket	2 x LGA 4710 (Socket E2)	Power Supply	3+1 2000W 80 PLUS Titanium redundant power supplies AC Input: 100-240V
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	8-Channel DDR5 RDIMM / MRDIMM, 32 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s [1] <small>[1] MRDIMMs are only supported with Intel® Xeon® 6 Processors with P-cores and in a 1DPC configuration.</small>	System Fans	4 x 80x80x80mm (17,500rpm)
LAN	2 x 10Gb/s LAN (1 x Intel® X550-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C~35°C, 8%~80% (non-condensing) Non-operating: -40°C~60°C, 20%~95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x XV24-SX0-AAJ1 2 x CPU heatsinks 1 x Mini-DP to D-Sub cable 2 x GPU power cables (12VHPWR, 620mm) 2 x GPU power cables (12VHPWR, 750mm) 4 x Carriers 1 x 3-Section Rail kit
Storage	Front hot-swap: 4 x 2.5" Gen5 NVMe/SATA/SAS-4 [1] Internal M.2: 2 x M.2 (2280/22110), PCIe Gen5 x2 <small>[1] Storage card is required to support SATA and SAS drives.</small>	Ordering Part Numbers	6NXV24SX0MR000AAJ1*
RAID	Require RAID add-in cards Onboard VROC key header	Optional Parts	- Chassis intrusion switch: 25HA1-R28390-U1R - Cable Management Arm: 25HB2-2AA700-K0R



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

