

# E133-C10-AAA1

## Edge Server - 1U UP 2-Bay SATA



### Features

- AMD EPYC™ 4004 / Ryzen™ 7000 Series Processors
- Single processor, 5nm technology
- Dual Channel ECC/Non-ECC DDR5 UDIMM, 4 x DIMMs
- 2 x 1Gb/s LAN ports (Broadcom® BCM5720)
- 1 x Dedicated management port
- 2 x 2.5" SATA hot-swappable bays
- 1 x M.2 slot with PCIe Gen4 x4 interface
- 1 x FHFL PCIe Gen5 x16 slot
- 1 x FHHL PCIe Gen4 x4 slot
- 1+1 550W 80 PLUS Platinum redundant power supplies

### Application

Networking, Edge, Hybrid/Private Cloud Server

### Specification

<b>Dimensions</b>	1U (W438 x H43.5 x D710 mm)	<b>Backplane I/O</b>	SATA 6Gb/s
<b>Motherboard</b>	MC13-BL1	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010)
<b>CPU</b>	AMD EPYC™ 4004 Series Processors AMD Ryzen™ 7000 Series Processors Single processor, 5nm technology, Socket AM5 TDP up to 105W	<b>Power Supply</b>	1+1 550W 80 PLUS Platinum redundant power supplies AC Input: 100-240V
<b>Chipset</b>	AMD B650E	<b>System Management</b>	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Memory</b>	2-Channel DDR5 memory, 4 x DIMM slots DIMM modules up to 32GB supported ECC Unbuffered DIMM 1Rx8/2Rx8 modules supported Non-ECC Unbuffered DIMM 1Rx8/2Rx8/1Rx16 modules supported Memory speed: up to 5200 MHz (1DPC), 3600 MHz (2DPC)	<b>OS Compatibility</b>	<b>EPYC 4004 Series:</b> Ubuntu 22.04 / Ubuntu 24.04 Windows Server 2022 <b>Ryzen 7000 Series:</b> Windows 10 21H2 / Windows 11
<b>LAN</b>	2 x 1GbE LAN ports (2 x Broadcom® BCM5720) Supported NCSI function 1 x 10/100/1000 Management LAN	<b>System Fans</b>	3 x 40x40x56mm (29,700rpm)
<b>Video</b>	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>Operating Properties</b>	Operating temperature: 10°C to 30°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Storage</b>	2 x 2.5" SATA hot-swappable bays SATA supported only	<b>Packaging Content</b>	1 x E133-C10-AAA1 1 x CPU heatsink 1 x Mini-DP to D-Sub cable
<b>RAID</b>	RAID 0/1	<b>Reference Numbers</b>	Barebone package (EPYC/Ryzen): 6NE133C10MR000ABA1* Barebone package (Ryzen): 6NE133C10MR000AAA1* - Motherboard: 9MC13BL1NR-000 - CPU heatsink: 25ST1-121100-A7R - Mini-DP to D-Sub cable: 25CRN-200801-K1R - Power supply: 25EPO-205502-F3S - 2-Section Rail kit (385-480mm): 25HB2-3A0204-K0R (Optional) - 2-Section Rail kit (660-840mm): 25HB2-3A0203-K0R (Optional)
<b>Expansion Slots</b>	1 x PCIe x16 (Gen5 x16) FHFL slot 1 x PCIe x4 (Gen4 x4) FHHL slot 1 x M.2 slot (M-key, PCIe Gen4 x4, supports 2280/22110 cards)		
<b>Front I/O</b>	1 x USB 3.2 Gen1		
<b>Rear I/O</b>	2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server at <https://www.gigacomputing.com>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* AMD, the AMD Arrow logo, EPYC, Ryzen and combinations thereof are trademarks of Advanced Micro Devices, Inc. All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

