


E163-P30-AAG1

Edge Server - 1U UP 2-Bay SATA/SAS-4



Features

- Single AmpereOne® Family Processors
- 8-Channel DDR5 RDIMM, 16 x DIMMs
- Dual ROM Architecture
- 1 x 1Gb/s LAN port via Intel® I210-AT
- 2 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen5 x4 interface
- 2 x FHHL PCIe Gen5 x16 slots
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- 2 x 800W 80 PLUS Titanium redundant power supply

Application

Networking, Edge, Hybrid/Private Cloud Server...

Specification

Dimensions	1U (W438 x H43.5 x D520 mm)	I/O Ports	Front: 1 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x RJ45, 1 x Mini-DP, 1 x MLAN
Motherboard	MP33-DC0	Backplane Board	Speed and bandwidth: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
CPU	AmpereOne® Family Processors Up to 192 custom cores Single processor, TDP up to 400W	Security Modules	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM010
Sock	1 x LGA 5964	Power Supply	2 x 800W 80 PLUS Titanium redundant power supply AC Input: 100-240V
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	16 x DIMM slots 8-Channel DDR5 memory architecture RDIMM: Up to 5200 MT/s, 4400 MT/s (2R 2DPC)	System Fans	5 x 40x40x56mm (30,000rpm)
LAN	1 x 1Gb/s LAN port (Intel® I210-AT) - Supports NCSI function 1 x 10/100/1000 Mbps management LAN	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x E163-P30-AAG1, 1 x CPU heatsink, 1 x Carrier, 1 x Mini-DP to D-Sub cable Packaging Dimensions: 782 x 588 x 212 mm
Storage	Front hot-swap: 2 x 2.5" Gen5 NVMe/SATA/SAS-4* *SAS card is required to support SAS drives. Internal M.2: 1 x M.2 (2280/22110), PCIe Gen5 x4	Part Numbers	Barebone package: 6NE163P30DR000ABG1* Optional parts: - 2-Section Rail kit (385-480mm): 25HB2-3A0204-K0R - 2-Section Rail kit (660-840mm): 25HB2-3A0203-K0R
RAID	Require RAID add-in cards		
Expansion Slots	2 x FHHL PCIe Gen5 x16 slots 2 x OCP NIC 3.0 PCIe Gen5 x16 slots		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* Ampere, AmpereOne and Ampere logos are registered trademarks or trademarks of Ampere Computing.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

