


## G262-Z00

HPC System - 2U DP AMD OAM 4 GPU Server



### Features

- Supports 4 x AMD Instinct™ MI250 OAM GPU modules
- Supports AMD Infinity Fabric Links technology
- Dual AMD EPYC™ 7003 series processor family
- 8-Channel RDIMM/LRDIMM DDR4, 16 x DIMMs
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x dedicated management port
- 4 x 2.5" Gen4 U.2 NVMe/SATA/SAS hot-swap HDD/SSD bays
- Ultra-Fast M.2 with PCIe Gen4 x4 interface
- 6 x Low profile Gen4 x16 expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 3000W 80 PLUS Platinum redundant power supply

### Specification

<b>Dimensions</b>	2U (W448 x H86.8 x D850 mm)	<b>Backplane I/O</b>	4 x 2.5" NVMe/ SATA hybrid ports Speed and bandwidth: PCIe Gen4 or SATA 6Gb/s
<b>Motherboard</b>	MZ62-HD5 Rev. 3.0	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>CPU</b>	AMD EPYC™ 7003 Series processors Single processor, 7nm technology Up to 64-core, 128 threads per processor cTDP up to 280W Compatible with AMD EPYC™ 7002 Series processors	<b>Power Supply</b>	2 x 3000W redundant power supply AC Input: 115-240V
<b>Chipset</b>	System on Chip	<b>System Management</b>	Aspeed® AST2500 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Memory</b>	8-Channel DDR4 memory, 16 x DIMM slots RDIMM/LRDIMM modules up to 128GB supported 3DS RDIMM/LRDIMM modules up to 256GB supported Memory speed: Up to 3200 MHz	<b>OS Compatibility</b>	Windows Server 2016 / 2019 RHEL 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 18.04.5 LTS (x64) / 20.04 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update1 or later Citrix Hypervisor 8.2.0 or later
<b>LAN</b>	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	<b>System Fans</b>	2 x 60x60x76mm (21,700rpm) 5 x 80x80x80mm (17,000rpm)
<b>Video</b>	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Storage</b>	4 x 2.5" Gen4 U.2 NVMe/ SATA/ SAS hot-swap HDD/SSD bays SAS card is required for SAS devices support	<b>Package Contents</b>	1 x G262-Z00 2 x CPU fan-sinks 1 x Rail kit
<b>Expansion Slots</b>	Pre-installed with 4 x AMD MI250 OAM GPU modules 6 x Low profile PCIe Gen4 x16 expansion slots 1 x OCP 3.0 mezzanine slot with PCIe Gen4 x16 bandwidth 3 x M.2 slots with PCIe Gen4 x4 bandwidth	<b>Reference Numbers</b>	Barebone with rail kit: 6NG262Z00MR-00-A00 - Rail kit: 25HB2-A86102-K0R - CPU fan-sink: 25ST1-3532G0-M1R/25ST1-3532G1-M1R - Power supply: 25EP0-230003-D0S
<b>Front I/O</b>	1 x USB 3.0, 1 x mini-DP, 2 x RJ45, 1 x MLAN		
<b>Rear I/O</b>	N/A		



Learn more about GIGABYTE server solutions, visit [www.gigabyte.com/Enterprise](http://www.gigabyte.com/Enterprise)

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* AMD, and the AMD Arrow logo, AMD EPYC, AMD Instinct and combinations thereof are trademarks of Advanced Micro Devices, Inc.

\* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.