

G293-S46-AAM1

HPC/AI Server - 2U DP 4 x PCIe Gen5 GPUs

intel
XEON



Features

- Supports up to 4 x Dual slot Gen5 GPUs
- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 16 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Broadcom® BCM57416
- 8 x 2.5" Gen5 NVMe/SATA/SAS hot-swappable bays
- 4 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x LP PCIe Gen5 x16 slots for add-in cards
- Dual 2200W 80 PLUS Titanium redundant power supply

Specification

Dimensions	2U (W448 x H87.5 x D800 mm)	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
Motherboard	MS43-G21	Power Supply	Dual 2200W 80 PLUS Titanium redundant power supply AC Input: 100-240V
CPU	5th/4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350W	System Management	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Socket	2 x LGA 4677 (Socket E)	OS Compatibility	Windows Server 2019 / 2022 RHEL 8.6 / 8.7 / 8.8 / 8.9 / 8.10 / 9.0 / 9.1 / 9.2 / 9.3 / 9.4 SLES 15 SP4 / SP5 / SP6 Ubuntu 22.04 / 22.04.1 / 22.04.2 / 22.04.3 / 22.04.4 / 24.04 LTS VMware ESXi 7.0 Update 3o / 8.0 Update 1, Update 2, Update 3 Citrix Hypervisor 8.2 LTSR CU1
Chipset	Intel® C741 Chipset	System Fans	4 x 80x80x80mm (16,500rpm)
Memory	8-Channel DDR5 memory, 16 x DIMM slots RDIMM up to 96GB supported 3DS RDIMM modules up to 256GB supported Memory speed: Up to 5600 MT/s	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
LAN	2 x 10Gb/s LAN ports (1 x Broadcom® BCM57416) - Supported NCSI 1 x 10/100/1000 management LAN	Packaging Content	1 x G293-S46-AAM1, 2 x CPU heatsinks, 6 x Carrier clips, 4 x GPU power cables (12VHPWR), 1 x L-shape Rail kit Packaging Dimensions: 1133 x 724 x 261 mm
Video	ASPEED® AST2600 Integrated 2D Graphic Adapter	Part Numbers	Barebone package (5th/4th Gen): 6NG293S46DR000ABM1* Barebone package (4th Gen): 6NG293S46DR000AAM1* - L-shape Rail kit: 25HB2-A86102-K0R (optional) - CPU heatsink: 25ST1-35320F-C1R/25ST1-453207-C1R (optional) - Power supply: 25EP0-22200A-G1S (optional) - C19 power cord 125V/15A (US): 25CP1-018000-Q0R (optional) - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R (optional) - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R (optional) - RMA packaging: 6NG293S46SR-RMA-A100 (optional)
Storage	8 x 2.5" Gen5 NVMe/SATA/SAS hot-swappable bays *SAS card is required to support SAS drives.		
RAID	Intel® SATA RAID 0/1/10/5 Support optional RAID add-in cards		
Expansion Slots	4 x PCIe Gen5 x16 FHFL slots for GPUs 2 x PCIe Gen5 x16 low-profile slots		
Internal I/O	1 x TPM header, 1 x VROC connector		
Rear I/O	2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN		
Backplane I/O	PCIe Gen5 x4 or SATA 6Gb/s or SAS 12Gb/s		



Learn more about GIGABYTE server at <https://www.gigabyte.com/Enterprise>

Designed by



* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.