

H273-Z81-AAN1

High Density Server - 2U 4-Node DP 8-Bay NVMe/SATA



Features

- 2U 4-node rear access server system
- Dual AMD EPYC™ 9005/9004 Series Processors per node
- 12-Channel DDR5 RDIMM, 24 x DIMMs per node
- Dual ROM Architecture
- 8 x 1Gb/s LAN ports via Intel® I350-AM2
- 8 x 2.5" Gen4 NVMe/SATA/SAS hot-swap bays
- 4 x M.2 slots with PCIe Gen4 x4 interface (optional)
- 8 x LP PCIe Gen5 x16 slots
- 4 x OCP NIC 3.0 PCIe Gen5 x16 slots
- Dual 2600W 80 PLUS Titanium redundant power supply

Application

HPC, HCI, Hybrid/Private Cloud Server

Specification

Dimensions	2U 4-Node - Rear access (W440 x H87.5 x D877 mm)	Backplane Board	Speed and bandwidth: PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
Motherboard	MZ83-HD0	TPM	4 x TPM headers with SPI interface - Optional TPM2.0 kit: CTM010
CPU	AMD EPYC™ 9005/9004 Series Processors Dual processor per node, cTDP up to 240W - With 1 x low-profile card at ambient 30°C, cTDP up to 300W - With OCP NIC 3.0 at ambient 25°C, cTDP up to 300W	Power Supply	Dual 2600W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
Socket	8 x LGA 6096 (Socket SP5)	System Management	ASPEED® AST2600 Baseboard Management Controller ASPEED® AST2520 Chassis Management Controller GIGABYTE Management Console web interface
Chipset	System on Chip	OS Support	Windows Server, Red Hat Enterprise Linux server, Ubuntu, SUSE Linux Enterprise server, VMware ESXi, Citrix Hypervisor
Memory	12-Channel DDR5 RDIMM, 96 x DIMMs [EPYC 9005] RDIMM: Up to 6000 MT/s [EPYC 9004] RDIMM: Up to 4800 MT/s	System Fans	4 x 80x80x80mm (16,900rpm)
LAN	8 x 1Gb/s LAN ports (1 x Intel® I350-AM2) - Support NCSI function 4 x 10/100/1000 management LAN	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in ASPEED® AST2600 x 4 - 4 x Mini-DP	Packaging Content	1 x H273-Z81-AAN1, 8 x CPU heatsinks 1 x Mini-DP to D-Sub cable, 1 x 3-Section Rail kit Packaging Dimensions: 1179 x 700 x 380 mm
Storage	Front hot-swap: 8 x 2.5" Gen4 NVMe/SATA/SAS *SAS card is required to support SAS drives. Optional internal M.2: 4 x M.2 (2280/22110)	Part Numbers	Barebone package: 6NH273Z81DR000ACN1* Optional parts: - C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R - M.2 expansion card - CMTP192: 9CMTP192NR-00* - RMA packaging: 6NH273Z81SR-RMA-A100
RAID	Require RAID add-in cards		
Expansion Slots	8 x LP PCIe Gen5 x16 slots 4 x OCP 3.0 PCIe Gen5 x16 slots		
Rear I/O	8 x USB 3.2 Gen1, 4 x Mini-DP, 8 x RJ45, 4 x MLAN		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

