R113-C10-AA01

Rack Server - 1U UP 4-Bay SATA







Features

- AMD Ryzen™ 7000 Series processors
- · Single processor, 5nm technology
- Dual Channel ECC/Non-ECC DDR5 UDIMM, 4 x DIMMs
- 2 x 1Gb/s LAN ports
- 1 x Dedicated management port
- 2 x 2.5" SATA hot-swappable bays
- 2 x 2.5" SATA internal bays
- 1 x M.2 slot with PCle Gen5 x4 interface
- 1 x FHHL PCIe Gen5 x16 slot
- Single 350W 80 PLUS Bronze power supply

Specification

Dimensions	1U (W430 x H43.5 x D393.2 mm)	Rear I/O	2 x USB 3.2 Gen1, 1 x COM, 1 x VGA, 2 x RJ45, 1 x MLAN
Motherboard	MC13-LE0	Backplane I/O	N/A
CPU	AMD Ryzen [™] 7000 Series processors Single processor, 5nm technology, Socket AM5 TDP up to 105W	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
Chipset	AMD B650E	Power Supply	Single 350W 80 PLUS Bronze power supply AC Input: 100-240V
Memory	4 x DIMM slots, DDR5 memory supported only Dual Channel memory architecture DIMM modules up to 32GB supported ECC Unbuffered DIMM 1Rx8/2Rx8 modules supported Non-ECC Unbuffered DIMM 1Rx8/2Rx8/1Rx16 modules supported Memory speed: up to 5200 MHz (1DPC), 3600 MHz (2DPC)	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
		OS Compatibility	Windows 10 21H2 (x64) Windows 11 (x64)
LAN	2 x 1Gb/s LAN ports (2 x Intel I210-AT) - Support NCSI 1 x 10/100/1000 management LAN	System Fans	3 x 40x40x56mm (29,700rpm)
LAN		Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM		
Storage	Front side: 2 x 2.5" SATA hot-swappable bays Internal: 2 x 2.5" SATA bays SATA supported only; RAID 0/1/10	Packaging Content	1 x R113-C10 1 x CPU heatsink
		Reference Numbers	Barebone package: 6NR113C10MR000AA01*
Expansion Slots	1 x FHHL PCIe Gen5 x16 slot 1 x M.2 slot: M-key, PCIe Gen5 x4, supports 2242/2280 cards	Name of the second	- Motherboard: 9MC13LE0NR-000 - CPU heatsink: 25ST1-121101-A7R - Riser card - CRS101R: 9CRS101RNR-00 - Power supply: 25EP0-203509-F3S
Front I/O	2 x USB 3.2 Gen1		



Learn more about GIGABYTE server, visit https://www.gigacomputing.com

- * All specifications are subject to change without notice. Please visit our website for the latest information.
- * AMD, the AMD Arrow logo, RYZEN and combinations thereof are trademarks of Advanced Micro Devices, Inc.
- * All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved



Engineered by







