

# R152-P30

## ARM Server - 1U UP 10-Bay Rack Server



AMPERE®



### Features

- Hardware-level root of trust support
- Single socket Ampere® Altra® Processor
- 8-Channel RDIMM/LRDIMM DDR4, 16 x DIMMs
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 6 x SATA/SAS and 4 x NVMe 2.5" hot-swap HDD/SSD bays
- 2 x Ultra-Fast M.2 with PCIe Gen4 x4 interface
- 1 x PCIe Gen4 x16 expansion slot
- Aspeed® AST2500 management controller
- 650W 80 PLUS Platinum redundant power supply

### Specification

<b>Dimensions</b>	1U (W438 x H43.5 x D660 mm)	<b>Backplane I/O</b>	Backplane P/N: 9CBP10A3NR-00 Speed and bandwidth: PCIe Gen3 x4, SAS 12Gb/s, SATA 6Gb/s
<b>Motherboard</b>	MP32-AR1	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>CPU</b>	Ampere® Altra® Processor Single processor, 7nm technology, LGA4926 socket Up to 80-core per processor	<b>Power Supply</b>	Dual 650W 80 PLUS Platinum redundant power supply AC Input: 100-240V
<b>Chipset</b>	System on Chip	<b>System Management</b>	Aspeed® AST2500 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Memory</b>	8-Channel DDR4 memory, 16 x DIMM slots RDIMM/LRDIMM modules up to 256GB supported Up to 4TB of memory capacity supported per processor Memory speed: Up to 3200 MHz NOTE: Only supports configurations with 1, 2, 4, 6, 8, 12, or 16 DIMMs	<b>OS Compatibility</b>	RHEL 8.3 (ARM64) CentOS 8.3-2011 (ARM64) SLES 15 SP2 (ARM64) Ubuntu 18.04.5-server / 20.04.1-legacy-server (ARM64) Fedora Server 33-1.2 (ARM64) FreeBSD 13.0 current (ARM64) OracleLinux R8 U2 (ARM64) Debian 10.9 (Buster) (ARM64)
<b>LAN</b>	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	<b>System Fans</b>	5 x 40x40x56mm (23'000rpm)
<b>Video</b>	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Storage</b>	6 x 2.5" SATA/SAS hot-swappable HDD/SSD bays from CRAO338 SAS RAID Card 4 x 2.5" NVMe hot-swappable HDD/SSD bays	<b>Packaging Content</b>	1 x R152-P30 system 1 x CPU heatsink 1 x Rail kit
<b>SAS</b>	Supported	<b>Reference Numbers</b>	Barebone package: 6NR152P30MR-00 - Motherboard: 9MP32AR1NR-00 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-2534Z0-C1R - OCP type SAS RAID Card: 9CRAO338NR-00 - Power supply module: 25EP0-206506-F3S
<b>RAID</b>	RAID 0/ 1/ 1E/ 10		
<b>Expansion Slots</b>	1 x PCIe x16 slot (4.0 x16), Full height half-length 1 x OCP 2.0 mezzanine slot, occupied by CRAO338 RAID card 2 x M.2 slots (4.0 x4), supports 2242/2260/2280/22110 cards		
<b>Front I/O</b>	1 x USB 3.0		
<b>Rear I/O</b>	3 x USB 3.0, 1 x VGA, 1 x COM, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server solutions, visit [www.gigabyte.com/Enterprise](http://www.gigabyte.com/Enterprise)

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* Ampere, Altra and Ampere logos are registered trademarks or trademarks of Ampere Computing.

\* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.