

R152-P32

Arm-based Rack Server - 1U UP 8-Bay NVMe



Features

- Hardware-level root of trust support
- Single socket Ampere® Altra® Max or Altra® Processor
- 8-Channel RDIMM/LRDIMM DDR4, 16 x DIMMs
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 8 x 2.5" Gen4 NVMe hot-swappable SSD bays
- 2 x Ultra-Fast M.2 with PCIe Gen4 x4 interface
- Aspeed® AST2500 management controller
- 1100W (240V) 80 PLUS Platinum redundant power supply

Specification

Dimensions	1U (W438 x H43.5 x D660 mm)	Backplane I/O	Backplane P/N: 9CBP10A5NR-00 Speed and bandwidth: PCIe Gen4 x4
Motherboard	MP32-AR2	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
CPU	Ampere® Altra® Max or Altra® Processor Single processor, 7nm technology Up to 128-core per processor NOTE: supports CPU Q80-33 at ambient 30°C	Power Supply	Dual 1100W 80 PLUS Platinum redundant power supply AC Input: 100-240V
Chipset	System on Chip	System Management	Aspeed® AST2500 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Memory	8-Channel DDR4 memory, 16 x DIMM slots RDIMM/LRDIMM modules up to 256GB supported Up to 4TB of memory capacity supported per processor Memory speed: Up to 3200 MHz NOTE: Only supports configurations with 1, 2, 4, 6, 8, 12, or 16 DIMMs	OS Compatibility	RHEL 8.3 / 8.5 (AArch64) CentOS 8.3-2011 / 8.4.2105 / 8.5.2111 (AArch64) SLES 15 SP2 / 15 SP3 (AArch64) Ubuntu 18.04.5 LTS / 20.04.1 LTS (AArch64) Fedora Server 33-1.2 / 35-1.2 (AArch64) OracleLinux R8 U2 / R8 U5 Debian 10.9 (Buster) / 11.1 (AArch64)
LAN	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	System Fans	6 x 40x40x56mm (23,000rpm)
Video	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Storage	8 x 2.5" Gen4 NVMe hot-swap SSD bays from onboard NVMe ports non-supported SATA devices	Packaging Content	1 x R152-P32, 1 x CPU heatsink, 1 x Rail kit
SAS	N/A	Reference Numbers	Barebone package: 6NR152P33MR-00 - Motherboard: 9MP32AR2NR-00 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-2534Z0-C1R - Power supply: 25EP0-201102-F3S
Expansion Slots	1 x PCIe Gen4 x16 FHHL slot 2 x M.2 slots (PCIe Gen4 x4, supports 2242/2260/2280/22110 cards)		
Front I/O	1 x USB 3.2 Gen1		
Rear I/O	3 x USB 3.2 Gen1, 1 x VGA, 1 x COM, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server solutions, visit www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.

* Ampere, Altra and Ampere logos are registered trademarks or trademarks of Ampere Computing.

* All other brands, logos and names are property of their respective owners.

© 2022 GIGABYTE Technology Co., Ltd. All rights reserved.