


R263-P30-AAH1

Rack Server - 2U UP 12-Bay NVMe/SATA



Features

- Single AmpereOne® Family Processors
- 8-Channel DDR5 RDIMM, 16 x DIMMs
- Dual ROM Architecture
- 1 x 1Gb/s LAN port via Intel® I210-AT
- 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 8 x 3.5"/2.5" SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen5 x4 interface
- 3 x FHHL PCIe Gen5 x16 slots
- 1 x FHHL PCIe Gen5 x8 slot
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- 2 x 1300W 80 PLUS Titanium redundant power supply

Application

Networking, Hybrid/Private Cloud Server...

Specification

Dimensions	2U (W438 x H87.5 x D710 mm)	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x RJ45, 1 x Mini-DP, 1 x MLAN
Motherboard	MP33-DC0	Backplane Board	Speed and bandwidth: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
CPU	AmpereOne® Family Processors Up to 192 custom cores Single processor, TDP up to 400W	Security Modules	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM010
Sock	1 x LGA 5964	Power Supply	2 x 1300W 80 PLUS Titanium redundant power supply AC Input: 100-240V
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	16 x DIMM slots 8-Channel DDR5 memory architecture RDIMM: Up to 5200 MT/s, 4400 MT/s (2R 2DPC)	System Fans	4 x 80x80x38mm (18,300rpm)
LAN	1 x 1Gb/s LAN port (Intel® I210-AT) - Supports NCSI function 1 x 10/100/1000 Mbps management LAN	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x R263-P30-AAH1, 1 x CPU heatsink, 1 x Carrier, 1 x Mini-DP to D-Sub cable, 1 x 2-Section Rail kit Packaging Dimensions: 989 x 594 x 279 mm
Storage	Front hot-swap: 4 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4* 8 x 3.5"/2.5" SATA/SAS-4* *SAS card is required to support SAS drives. Internal M.2: 1 x M.2 (2280/22110), PCIe Gen5 x4	Part Numbers	Barebone package: 6NR263P30DR000ABH1* Optional parts: - 3-Section Rail kit: 25HB2-A56121-K0R - Cable Management Arm: 25HB1-R18300-K0R
RAID	Require RAID add-in cards		
Expansion Slots	3 x FHHL PCIe Gen5 x16 slots 1 x FHHL PCIe Gen5 x8 slot 2 x OCP NIC 3.0 PCIe Gen5 x16 slots		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* Ampere, AmpereOne and Ampere logos are registered trademarks or trademarks of Ampere Computing.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

