


R264-AG0-AAS1

Rack Server - 2U UP 4 x PCIe Gen5 GPUs



Key Features

- Supports up to 4 x Dual slot Gen5 GPUs
- Single Intel® Xeon® 6 Processors, LGA 7529
- 12-Channel DDR5 RDIMM / MCR DIMM, 12 x DIMMs
- Dual ROM Architecture
- 2 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 10 x 3.5"/2.5" SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen5 x2 interface
- 4 x FHFL PCIe Gen5 x16 slots for GPUs
- 1 x OCP NIC 3.0 PCIe Gen5 x16 slot
- 2 x 3200W 80 PLUS Titanium redundant power supply

Application

AI, AI Inference, Visual Computing, Networking, Hybrid/Private Cloud...

Specification

Dimensions	2U (W438 x H87.5 x D815 mm)	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 1 x MLAN
Motherboard	MAG4-GU0	Backplane Board	Gen5 NVMe or SATA 6Gb/s or SAS-4 24Gb/s
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6900-Series Processors Single processor, TDP up to 500W	Security Modules	1 x TPM header with SPI interface - Optional TPM2.0 kit: CTM012 1 x PRoT module connector (only enabled on RoT SKU)
Socket	1 x LGA 7529 (Socket BR)	Power Supply	2 x 3200W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
Chipset	System on Chip	System Management	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Memory	12-Channel DDR5 RDIMM / MCR DIMM*, 12 x DIMM slots RDIMM: Up to 6400 MT/s MCR DIMM: Up to 8000 MT/s *MCR DIMMs are only supported with Intel Xeon 6 CPU with P-cores.	System Fans	4 x 80x80x56mm (15,500rpm)
LAN	1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating temperature: 10°C to 30°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x R264-AG0-AAS1, 1 x CPU heatsink, 1 x Carrier, 1 x Mini-DP to D-Sub cable, 4 x GPU power cables
Storage	Front hot-swap: 2 x 3.5"/2.5" Gen5 NVMe/SATA/SAS-4* 10 x 3.5"/2.5" SATA/SAS-4* *SAS card is required to support SAS drives. Internal M.2: 1 x M.2 (2280/22110), PCIe Gen5 x2	Part Numbers	Barebone package: 6NR264AG0DR000AAS1* Optional parts: - C19 power cord 125V/15A (US): 25CP1-018000-Q0R - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R - C19 power cord 125V/15A (JP): 25CPA-01830B-Q0R - 3-Section Rail kit (Supports CMA): 25HB2-A56121-K0R - Cable Management Arm: 25HB1-R18300-K0R
RAID	Require RAID add-in cards Onboard VROC key header		
Expansion Slots	4 x FHFL PCIe Gen5 x16 slots for GPUs 1 x OCP NIC 3.0 PCIe Gen5 x16 slot (supports NCSI function)		



Learn more at <https://www.GIGABYTE.com/enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* All other brands, logos and names are property of their respective owners.

© 2024 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

