

R282-3C2

Intel Xeon Rack Server - 2U DP 14-Bay



Features

- 3rd Gen. Intel® Xeon® Scalable Processors
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 32 x DIMMs
- Dual ROM technology supported
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 8 x 3.5" or 2.5" SATA/SAS hot-swappable HDD/SSD bays
- 4 x 3.5" or 2.5" SATA/SAS/Gen4 NVMe hot-swap HDD/SSD bays
- 2 x 2.5" SATA/SAS hot-swappable HDD/SSD bays in rear side
- 8 x PCIe Gen4 x16 expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 1 x OCP 2.0 Gen3 x8 mezzanine slot
- 1600W (240V) 80 PLUS Platinum redundant power supply

Specification

Dimensions	2U (438 x 43.5 x 730 mm)	Front I/O	2 x USB 3.0
Motherboard	MR92-FS0	Rear I/O	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN
CPU	3rd Gen Intel® Xeon® Scalable Processors 10nm technology, CPU TDP up to 270W 2 x LGA 4189 sockets (Socket P+)	Backplane I/O	Front_CBP20C5: 8 x SATA/SAS and 4 x SATA/SAS/NVMe ports Rear_CBP2022: 2 x SATA ports Bandwidth: PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
Chipset	Intel® C621A Express Chipset	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
Memory	8-Channel DDR4 memory, 32 x DIMM slots RDIMM modules up to 64GB supported LRDIMM modules up to 128GB supported 3DS RDIMM/LRDIMM modules up to 256GB supported 1.2V modules: 3200/2933/2666 MHz	Power Supply	1+1 1600W (240V) 80 PLUS Platinum redundant power supply AC Input: 100-240V
LAN	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Video	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	OS Compatibility	Windows Server 2016 / 2019 RHEL 8.2 (x64) / 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 20.04 LTS (x64) / 20.04.1 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update2 or later Citrix Hypervisor 8.2.0
Storage	8 x 3.5" or 2.5" SATA/SAS hot-swappable HDD/SSD bays 4 x 3.5" or 2.5" SATA/SAS/Gen4 NVMe hot-swap HDD/SSD bays 2 x 2.5" SATA/SAS hot-swappable HDD/SSD bays in rear side	System Fans	4 x 80x80x38mm (16,300rpm)
RAID	Intel® SATA RAID 0, 1, 10, 5 Intel® Virtual RAID On CPU (VROC) RAID 0, 1, 10, 5 Note: VROC module is compatible for Intel®SSD only	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Expansion Slots	1 x PCIe x16 slot (Gen4 x16), FHHL 2 x PCIe x16 slots (Gen4 x16 or x8), FHHL 2 x PCIe x8 slots (Gen4 x8), FHHL 1 x PCIe x8 slots (Gen4 x0 or x8), FHHL 2 x PCIe x8 slots (Gen4 x8), LPHL 1 x OCP 3.0 mezzanine slot (Gen4 x16) - Supported NCSI function 1 x OCP 2.0 mezzanine slot (Gen3 x8) - Supported NCSI function	Packaging Content	1 x R282-3C2, 2 x CPU heatsinks, 1 x Rail kit 1 x VROC module
		Reference Numbers	Barebone package: 6NR2823C2MR-00 - Motherboard: 9MR92FS1NR-00 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-343102-M1R - Power supply: 25EP0-216008-L0S



Learn more about GIGABYTE server solutions, visit www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.